

ACER : Rack Servers



* Service by Acer Care เฉพาะกรุงเทพฯ & ปริมณฑล นอกพื้นที่โปรดติดต่อฝ่ายขาย



Altos BrainSphere™ R380F5

ACR-USRSKST002



Altos BrainSphere™ R320 F5

ACR-USRJVST00E

CPU	1 x Intel® Xeon® Silver 4316 Processor 30M Cache, 2.30 GHz	1 x Intel® Xeon® E-2224 Processor 8M Cache, 3.40 GHz
Memory	32GB (2x16GB) DDR4-3200 ECC RDIMM	16GB (1x16GB) DDR4-2666 ECC UDIMM
Expansion Slots	1 PCI-E 4.0 x16 (FH) 5 PCI-E 4.0 x8 (FH) (PCIe4.0x16 options available) 1 PCI-E 4.0 x16 (LP) 1 PCI-E 4.0 x8 (Internal LP)	1 x PCI-E 3.0 x8 1 x M.2 2280/22110 slot (M-key, w/PCIe 3.0 x4)
Harddisk	2 x 2.5" 600GB SAS 10KRPM Hard Drive	2 x 1TB 3.5" SATA 7200 RPM
Chipset	Intel® C621A	Intel® C242
RAID Controller	HW RAID 0/1/10/5/50 Low-Profile PCI-E x8 8-port	Integrated SATA RAID supports RAID 0, 1, 5, 10 on Windows® OS only
Optical device	No	4 x 3.5" SAS/SATA hot-swappable bays for HDD/SSD
Onboard Gigabit Ethernet	2-port 10GbE RJ-45 LAN Card	No
Redundant Power Supply	Yes (1200W)	2 x RJ45 Ethernet LAN ports
Form Factor	2U Rack	Yes (300W)
OS Support (Not Provide OS)	Microsoft® Windows Server® 2019 Red Hat® Enterprise Linux® 8.0 VMware ESXi 6.7 and 7.0	Microsoft® Windows Server® 2019 Red Hat® Enterprise Linux®
Mouse	Altos USB Mouse	Altos USB Mouse
Keyboard	Altos USB Keyboard	Altos USB Keyboard
Warranty	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand	3 Year warranty Part & Labor, 5x8, Onsite Service NBD Thailand
SRP (inc. VAT)	310,086.-	77,361.-

DELL EMC : Rack Servers



PowerEdge R440

DEL-SNSR4404110



PowerEdge R440

DEL-SNSR4403106



PowerEdge R440

DEL-SNSR4404116

Form Factor	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives +	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives +	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives +
Processor	1 x Intel® Xeon® Silver 4110	1 x Intel® Xeon® Bronze 3106	2 x Intel® Xeon® Silver 4116
Processor Speed / Core	2.1G, 8C/16T, 9.6GT/s 2UPI, 11M Cache, Turbo, HT (85W)	1.7G, 8C/8T, 9.6GT/s 2UPI, 11M Cache, No Turbo, No HT (85W)	2.1G, 12C/24T, 9.6GT/s 2UPI, 16.5M Cache, Turbo, HT (85W)
Memory	DDR4-2400, 16GB (1x16GB) RDIMM, 2666MT/s, Dual Rank	8GB (1x8GB) RDIMM, 2666MT/s, Dual Rank	32GB (2x16GB) RDIMM, 2666MT/s, Dual Rank
Network	Dual-Port 1GbE On-Board LOM	Dual-Port 1GbE On-Board LOM	Dual-Port 1GbE On-Board LOM
Harddisk	2 x 1.2TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive	2 x 1TB 7.2K RPM NLSAS 12Gbps 512n 2.5in Hot-plug Hard Drive	4 x 1TB 7.2K RPM NLSAS 12Gbps 512n 2.5in Hot-plug Hard Drive
RAID Controller	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache	PERC H730P+ Low Profile Adapter RAID Controller, 2Gb NV Cache
Optical Drive	DVD+/-RW, SATA	DVD+/-RW, SATA	DVD+/-RW, SATA
Power Supply	Dual, Hot-plug, Redundant Power Supply (1+1), 550W	Dual, Hot-plug, Redundant Power Supply (1+1), 550W	Dual, Hot-plug, Redundant Power Supply (1+1), 550W
System Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management	iDRAC9 Enterprise with OME Server Configuration Management
Warranty	3Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	133,750.-	107,000.-	208,650.-

DELL : Rack Servers

DELL Technologies



Dell PowerEdge R250

DEL-SnSR250A



Dell PowerEdge R250

DEL-SnSR250B



Dell PowerEdge R250

DEL-SnSR2501

Form Factor	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, PCIe 1 x16 and 1 x8x Slots	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, PCIe 1 x16 and 1 x8x Slots	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, PCIe 1 x16 and 1 x8x Slots
Processor	Intel® Xeon® E-2334	Intel® Xeon® E-2334	Intel® Xeon® E-2334
Processor Speed / Core	3.4GHz, 8M Cache, 4C/8T, Turbo (65W), 3200 MT/s	3.4GHz, 8M Cache, 4C/8T, Turbo (65W), 3200 MT/s	3.4GHz, 8M Cache, 4C/8T, Turbo (65W), 3200 MT/s
Memory	16GB (1x16GB) UDIMM, 3200MT/s, ECC	16GB (1x16GB) UDIMM, 3200MT/s, ECC	16GB (1x16GB) UDIMM, 3200MT/s, ECC
Network	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM
Hard disk Group#1	2x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 3.5in HYB CARR, 1 DWPD,	2x 4TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hard Drive	2x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 3.5in HYB CARR, 1 DWPD
Hard disk Group#2	N/A	N/A	N/A
RAID Controller	PERC H755 Controller Adapter, Low Profile Support RAID 0, 1, 5, 6, 10, 50, 60	PERC H755 Controller Adapter, Low Profile Support RAID 0, 1, 5, 6, 10, 50, 60	PERC H355 Adapter, Low Profile Support RAID 0, 1, 10
Optical Drive	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal
Power Supply	Single, Cabled Power Supply, 450W	Single, Cabled Power Supply, 450W	Single, Cabled Power Supply, 450W
System Management	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	90,348	87,641	80,578



Dell PowerEdge R250

DEL-SnSR2502



Dell PowerEdge R350

DEL-SnSR3501



Dell PowerEdge R350

DEL-SnSR350A

Form Factor	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, PCIe 1 x16 and 1 x8x Slots	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, ReadyRails™ Sliding Rails Without Cable Management Arm, PCIe 1 x8, 1 x16	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, ReadyRails™ Sliding Rails Without Cable Management Arm, PCIe 1 x8, 1 x16
Processor	Intel® Xeon® E-2334	Intel® Xeon® E-2336	Intel® Xeon® E-2336
Processor Speed / Core	3.4GHz, 8M Cache, 4C/8T, Turbo (65W), 3200 MT/s	2.9GHz, 12M Cache, 6C/12T, Turbo (65W), 3200 MT/s	2.9GHz, 12M Cache, 6C/12T, Turbo (65W), 3200 MT/s
Memory	16GB (1x16GB) UDIMM, 3200MT/s, ECC	16GB (1x16GB) UDIMM, 3200MT/s, ECC	16GB (1x16GB) UDIMM, 3200MT/s, ECC
Network	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM
Hard disk Group#1	2x 4TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hard Drive	2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-plug Hard Drive	2x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 3.5in HYB CARR, 1 DWPD,
Hard disk Group#2	N/A	N/A	N/A
RAID Controller	PERC H355 Adapter, Low Profile Support RAID 0, 1, 10	PERC H755 with front load bracket Support RAID 0, 1, 5, 6, 10, 50, 60	PERC H755 with front load bracket Support RAID 0, 1, 5, 6, 10, 50, 60
Optical Drive	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal
Power Supply	Single, Cabled Power Supply, 450W	Dual, Hot-Plug, Redundant Power Supply (1+1), 600W	Dual, Hot-Plug, Redundant Power Supply (1+1), 600W
System Management	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	80,822	102,797	104,552

DELL : Rack Servers



Dell PowerEdge R350

DEL-SnSR3502



Dell PowerEdge R350

DEL-SnSR3503



Dell PowerEdge R350

DEL-SnSR3505

Form Factor	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, ReadyRails™ Sliding Rails Without Cable Management Arm, PCIe 1 x8, 1 x16	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, ReadyRails™ Sliding Rails Without Cable Management Arm, PCIe 1 x8, 1 x16	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, ReadyRails™ Sliding Rails Without Cable Management Arm, PCIe 1 x8, 1 x16
Processor	Intel® Xeon® E-2336	Intel® Xeon® E-2336	Intel® Xeon® E-2336
Processor Speed / Core	2.9GHz, 12M Cache, 6C/12T, Turbo (65W), 3200 MT/s	2.9GHz, 12M Cache, 6C/12T, Turbo (65W), 3200 MT/s	2.9GHz, 12M Cache, 6C/12T, Turbo (65W), 3200 MT/s
Memory	16GB (1x16GB) UDIMM, 3200MT/s, ECC	16GB (1x16GB) UDIMM, 3200MT/s, ECC	16GB (1x16GB) UDIMM, 3200MT/s, ECC
Network	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM
Hard disk Group#1	2x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 3.5in HYB CARR, 1 DWPD,	2x 2TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-plug Hard Drive	2x 600GB Hard Drive SAS 12Gbps 15k 512n 2.5in with 3.5in HYB CARR Hot-Plug
Hard disk Group#2	2x 4TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-plug Hard Drive	N/A	N/A
RAID Controller	PERC H355 Adapter Support RAID 0, 1, 10	PERC H355 Adapter Support RAID 0, 1, 10	PERC H355 Adapter Support RAID 0, 1, 10
Optical Drive	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal
Power Supply	Dual, Hot-Plug, Redundant Power Supply (1+1), 600W	Dual, Hot-Plug, Redundant Power Supply (1+1), 600W	Dual, Hot-Plug, Redundant Power Supply (1+1), 600W
System Management	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	113,194	94,565	94,407



Dell PowerEdge R350

DEL-SnSR3506



Dell PowerEdge R350

DEL-SnSR3507



PowerEdge R450

DEL-SNSR45011

Form Factor	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, ReadyRails™ Sliding Rails Without Cable Management Arm, PCIe 1 x8, 1 x16	3.5" Chassis with up to 4 Hot Plug Hard Drives, TPM 2.0 V3, ReadyRails™ Sliding Rails Without Cable Management Arm, PCIe 1 x8, 1 x16	2.5" Chassis with up to 8 Hot Plug Hard Drives + Trusted Platform Module 2.0 V3, Quick Sync 2 + LCD Bezel + 1 xOCP 3.0(x16)+ 1 x16LP PCI Slot+ ReadyRails™ Sliding Rails With Cable Management Arm
Processor	Intel® Xeon® E-2336	Intel® Xeon® E-2336	1 x Intel® Xeon® Silver 4310
Processor Speed / Core	2.9GHz, 12M Cache, 6C/12T, Turbo (65W), 3200 MT/s	2.9GHz, 12M Cache, 6C/12T, Turbo (65W), 3200 MT/s	2.1G, 12C/24T, 10.4GT/s, 18M Cache, Turbo, HT (120W) DDR4-2666
Memory	16GB (1x16GB) UDIMM, 3200MT/s, ECC	16GB (1x16GB) UDIMM, 3200MT/s, ECC	32GB (1x32GB) RDIMM, 3200MT/s, Dual Rank
Network	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM	On-Board Broadcom 5720 Dual Port 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0
Hard disk Group#1	2x 4TB 7.2K RPM NLSAS ISE 12Gbps 512n 3.5in Hard Drive	2x 4TB 7.2K RPM NLSAS ISE 12Gbps 512n 3.5in Hard Drive	3x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
Hard disk Group#2	N/A	N/A	N/A
RAID Controller	PERC H755 with front load bracket Support RAID 0, 1, 5, 6, 10, 50, 60	PERC H355 Adapter Support RAID 0, 1, 10	PERC H755 with front load bracket
Optical Drive	DVD+/-RW, SATA, Internal	DVD+/-RW, SATA, Internal	8X DVD-ROM, USB, External
Power Supply	Dual, Hot-Plug, Redundant Power Supply (1+1), 600W	Dual, Hot-Plug, Redundant Power Supply (1+1), 600W	Dual, Hot-plug, Fully Redundant Power Supply (1+1), 800W, Mixed Mode
System Management	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	5Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive
SRP (inc. VAT)	104,741	100,338	160,301

DELL : Rack Servers

DELL Technologies



PowerEdge R450
DEL-SNSR45012



PowerEdge R450
DEL-SNSR45013



PowerEdge R450
DEL-SNSR45014

Form Factor	2.5" Chassis with up to 8 Hot Plug Hard Drives + Trusted Platform Module 2.0 V3, Quick Sync 2 + LCD Bezel + 1 xOCP 3.0(x16)+ 1 x16LP PCI Slot+ ReadyRails™ Sliding Rails With Cable Management Arm	2.5" Chassis with up to 8 Hot Plug Hard Drives + Trusted Platform Module 2.0 V3, Quick Sync 2 + LCD Bezel + 1 xOCP 3.0(x16)+ 1 x16LP PCI Slot + ReadyRails™ Sliding Rails With Cable Management Arm, No OCP 3.0 mezzanine NIC card, Blank Filler Only	2.5" Chassis with up to 8 Hot Plug Hard Drives + Trusted Platform Module 2.0 V3, Quick Sync 2 + LCD Bezel + 1xOCP 3.0(x16)+ 2 x16LP PCI Slot + ReadyRails™ Sliding Rails With Cable Management Arm
Processor	1 x Intel® Xeon® Silver 4310	1 x Intel® Xeon® Silver 4309Y	2 x Intel® Xeon® Silver 4314
Processor Speed / Core	2.1G, 12C/24T, 10.4GT/s, 18M Cache, Turbo, HT (120W) DDR4-2666	2.8G, 8C/16T, 10.4GT/s, 12M Cache, Turbo, HT (105W) DDR4-2666	2.4G, 16C/32T, 10.4GT/s, 24M Cache, Turbo, HT (135W) DDR4-2666
Memory	32GB (1x32GB) RDIMM, 3200MT/s, Dual Rank	32GB (1x32GB) RDIMM, 3200MT/s, Dual Rank	64GB (2x32GB) RDIMM, 3200MT/s, Dual Rank
Network	On-Board Broadcom 5720 Dual Port 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0	On-Board Broadcom 5720 Dual Port 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0	On-Board Broadcom 5720 Dual Port 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0
Hard disk Group#1	3x 960GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD,	3x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD	4x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
Hard disk Group#2	N/A	N/A	N/A
RAID Controller	PERC H755 with front load bracket	PERC H755 with front load bracket	PERC H755 with front load bracket
Optical Drive	8X DVD-ROM, USB, External	8X DVD-ROM, USB, External	8X DVD-ROM, USB, External
Power Supply	Dual, Hot-plug, Fully Redundant Power Supply (1+1), 800W, Mixed Mode	Dual, Hot-plug, Fully Redundant Power Supply (1+1), 800W, Mixed Mode	Dual, Hot-plug, Fully Redundant Power Supply (1+1), 800W, Mixed Mode
System Management	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced
Warranty	5Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive	5Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive	5Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive
SRP (inc. VAT)	169,792	161,154	227,078



PowerEdge R450
DEL-SNSR45015



PowerEdge R450
DEL-SNSR45016



PowerEdge R450
DEL-SNSR45017

Form Factor	2.5" Chassis with up to 8 Hot Plug Hard Drives + Trusted Platform Module 2.0 V3, Quick Sync 2 + LCD Bezel + 1xOCP 3.0(x16)+ 2x16LP PCI Slot + ReadyRails™ Sliding Rails With Cable Management Arm	3.5" Chassis with up to 4 Hot Plug Hard Drives + Trusted Platform Module 2.0 V3, Quick Sync 2 + LCD Bezel + 1xOCP 3.0(x16)+ 2x16LP PCI Slot + ReadyRails™ Sliding Rails With Cable Management Arm	2.5" Chassis with up to 8 Hot Plug Hard Drives + Trusted Platform Module 2.0 V3, Quick Sync 2 + LCD Bezel + 1 xOCP 3.0(x16)+ 1 x16LP PCI Slot+ ReadyRails™ Sliding Rails With Cable Management Arm
Processor	2 x Intel® Xeon® Silver 4314	2 x Intel® Xeon® Silver 4314	1 x Intel® Xeon® Silver 4314
Processor Speed / Core	2.4G, 16C/32T, 10.4GT/s, 24M Cache, Turbo, HT (135W) DDR4-2666	2.4G, 16C/32T, 10.4GT/s, 24M Cache, Turbo, HT (135W) DDR4-2666	2.4G, 16C/32T, 10.4GT/s, 24M Cache, Turbo, HT (135W) DDR4-2666
Memory	64GB (2x32GB) RDIMM, 3200MT/s, Dual Rank	64GB (2x32GB) RDIMM, 3200MT/s, Dual Rank	16GB (1x16GB) RDIMM, 3200MT/s, Dual Rank
Network	On-Board Broadcom 5720 Dual Port 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0	On-Board Broadcom 5720 Dual Port 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0	On-Board Broadcom 5720 Dual Port 1Gb LOM
Hard disk Group#1	4x 960GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD,	3x 960GB SSD SATA Mix Use 6Gbps 512 2.5in Hot-plug AG Drive, 3.5in HYB CARR, 3 DWPD,	2x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
Hard disk Group#2	N/A	N/A	N/A
RAID Controller	PERC H755 with front load bracket	PERC H755 with front load bracket	PERC H755 with front load bracket
Optical Drive	8X DVD-ROM, USB, External	DVD+/-RW, SATA	8X DVD-ROM, USB, External
Power Supply	Dual, Hot-plug, Fully Redundant Power Supply (1+1), 800W, Mixed Mode	Dual, Hot-plug, Fully Redundant Power Supply (1+1), 800W, Mixed Mode	Dual, Hot-plug, Fully Redundant Power Supply (1+1), 800W, Mixed Mode
System Management	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced
Warranty	5Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive	5Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive	5Yr ProSupport & Mission Critical:(7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive
SRP (inc. VAT)	242,616	245,396	160,246

DELL : Rack Servers

DELL Technologies

**PowerEdge R450**

DEL-SNSR45018

Dell PowerEdge R550

DEL-SNSR55011

Dell PowerEdge R650xs

DEL-SNSR65011

Form Factor	2.5" Chassis with up to 8 Hot Plug Hard Drives + Trusted Platform Module 2.0 V3, Quick Sync 2 + LCD Bezel + 1 xOCP 3.0(x16)+ 1 x16LP PCI Slot+ ReadyRails™ Sliding Rails With Cable Management Arm	2U, 3.5" Chassis with up to 8 Hot Plug Hard Drives, Trusted Platform Module 2.0 V3, + LCD Bezel + 1 x16 LP+ 1 x8(x4 link) LP PCI Slot, ReadyRails Sliding Rails with Cable Management Arm	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives, Trusted Platform Module 2.0 V3, + LCD Bezel + 1 xOCP 3.0(x16)+ 1 x16 LP PCI Slot, ReadyRails Sliding Rails with Cable Management Arm
Processor	1 x Intel® Xeon® Silver 4314	1 x Intel® Xeon® Silver 4310	1 x Intel® Xeon® Silver 4310T
Processor Speed / Core	2.4G, 16C/32T, 10.4GT/s, 24M Cache, Turbo, HT (135W) DDR4-2666	2.1G, 12C/24T, 10.4GT/s, 18M Cache, Turbo, HT (120W) DDR4-2666	2.3G, 10C/20T, 10.4GT/s, 15M Cache, Turbo, HT (105W) DDR4-2666
Memory	16GB (1x16GB) RDIMM, 3200MT/s, Dual Rank	32GB (1x 32GB) RDIMM, 3200MT/s, Dual Rank, 16Gb BASE	32GB (1x 32GB) RDIMM, 3200MT/s, Dual Rank, 16Gb BASE
Network	On-Board Broadcom 5720 Dual Port 1Gb LOM	2x 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0	2x 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0
Hard disk Group#1	2x 2.4TB 10K RPM SAS 12Gbps 512e 2.5in Hot-plug Hard Drive	3x 960GB SSD SATA Read Intensive 6Gbps 512e 2.5in Hot-plug, 3.5in HYB CARR S4510 Drive, 1 DWPD,	3x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
Hard disk Group#2	N/A	N/A	N/A
RAID Controller	PERC H755 with front load bracket	PERC H755 with front load bracket	PERC H755 with front load bracket
Optical Drive	8X DVD-ROM, USB, External	DVD +/-RW, SATA, Internal	8X DVD-ROM, USB, External
Power Supply	Dual, Hot-plug, Fully Redundant Power Supply (1+1), 800W, Mixed Mode	Dual, Hot-plug, Fully Redundant Power Supply (1+1), 800W, Mixed Mode	Dual, Hot-plug, Power Supply Fault Tolerant Redundant (1+1), 800W, Mixed Mode
System Management	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced
Warranty	5Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive	5Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive	5Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive
SRP (inc. VAT)	165,509	176,624	158,615

**Dell PowerEdge R650xs**

DEL-SNSR65012

Dell PowerEdge R650xs

DEL-SNSR65013

Dell PowerEdge R650xs

DEL-SNSR65014

Form Factor	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives, Trusted Platform Module 2.0 V3, + LCD Bezel +Riser Config 3, 1xOCP 3.0(x16)+ 2x16LP, ReadyRails Sliding Rails with Cable Management Arm	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives, Trusted Platform Module 2.0 V3, + LCD Bezel +Riser Config 3, 1xOCP 3.0(x16)+ 2x16LP, ReadyRails Sliding Rails with Cable Management Arm	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives, Trusted Platform Module 2.0 V3, + LCD Bezel + 1 xOCP 3.0(x16)+ 1 x16 LP PCI Slot, ReadyRails Sliding Rails with Cable Management Arm
Processor	2 x Intel® Xeon® Gold 6326	2 x Intel® Xeon® Gold 6326	1 x Intel® Xeon® Silver 4310T
Processor Speed / Core	2.9G, 16C/32T, 11.2GT/s, 24M Cache, Turbo, HT (185W) DDR4-3200	2.9G, 16C/32T, 11.2GT/s, 24M Cache, Turbo, HT (185W) DDR4-3200	2.3G, 10C/20T, 10.4GT/s, 15M Cache, Turbo, HT (105W) DDR4-2666
Memory	32GB (2x 16GB) RDIMM, 3200MT/s, Dual Rank, 16Gb BASE	32GB (2x 16GB) RDIMM, 3200MT/s, Dual Rank, 16Gb BASE	16GB (1x 16GB) RDIMM, 3200MT/s, Dual Rank, 16Gb BASE
Network	1x Broadcom 5720 Dual Port 1Gb On-Board LOM + Broadcom 57416 Dual Port 10GbE BASE-T Adapter, OCP NIC 3.0	1x Broadcom 5720 Dual Port 1Gb On-Board LOM + Broadcom 57416 Dual Port 10GbE BASE-T Adapter, OCP NIC 3.0	2x 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0
Hard disk Group#1	4 x 960GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD	4 x 2.4TB 10K RPM SAS ISE 12Gbps 512e 2.5in Hot-plug Hard Drive	2 x 960GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
Hard disk Group#2	N/A	N/A	N/A
RAID Controller	PERC H755 with front load bracket	PERC H755 with front load bracket	PERC H755 with front load bracket
Optical Drive	8X DVD-ROM, USB, External	8X DVD-ROM, USB, External	8X DVD-ROM, USB, External
Power Supply	Dual, Redundant(1+1), Hot-Plug Power Supply, 1100W MM(100-240Vac) Titanium	Dual, Redundant(1+1), Hot-Plug Power Supply, 1100W MM(100-240Vac) Titanium	Dual, Hot-plug, Power Supply Fault Tolerant Redundant (1+1), 800W, Mixed Mode
System Management	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive
SRP (inc. VAT)	305,068	304,449	155,444



SIS Distribution (Thailand) Public Company Limited
TEL. 02-020-3000
Email address : sis@sisthai.com

บริษัทฯ ขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว

DELL : Rack Servers



Dell PowerEdge R650xs

DEL-SNSR65015

Dell PowerEdge R750

DEL-SNSR750A

Dell PowerEdge R750

DEL-SNSR750B

Form Factor	1U, 2.5" Chassis with up to 8 Hot Plug Hard Drives, Trusted Platform Module 2.0 V3, + LCD Bezel + 1 xOCP 3.0(x16)+ 1 x16 LP PCI Slot, ReadyRails Sliding Rails with Cable Management Arm	2U, 2.5" Chassis with up to 24 Hot Plug Hard Drives, Trusted Platform Module 2.0 V3, + LCD Bezel + 2 x8, 2 x16 PCI slots, ReadyRails Sliding Rails with Cable Management Arm	2U, 2.5" Chassis with up to 16 Hot Plug Hard Drives, Trusted Platform Module 2.0 V3, + LCD Bezel + 6 x8, 2 x16 PCI slots, ReadyRails Sliding Rails with Cable Management Arm
Processor	1 x Intel® Xeon® Silver 4310T	1 x Intel® Xeon® Gold 5317	2 x Intel® Xeon® Gold 5317
Processor Speed / Core	2.3G, 10C/20T, 10.4GT/s, 15M Cache, Turbo, HT (105W) DDR4-2666	3G, 12C/24T, 11.2GT/s, 18M Cache, Turbo, HT (150W) DDR4-2933	3G, 12C/24T, 11.2GT/s, 18M Cache, Turbo, HT (150W) DDR4-2933
Memory	16GB (1x 16GB) RDIMM, 3200MT/s, Dual Rank, 16Gb BASE	32GB (1x 32GB) RDIMM, 3200MT/s, Dual Rank, 16Gb BASE	64GB (2x 32GB) RDIMM, 3200MT/s, Dual Rank, 16Gb BASE
Network	2x 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0	2x 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0	2x 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0
Hard disk Group#1	2 x 1.2TB Hard Drive ISE SAS 12Gbps 10k 512n 2.5in Hot-Plug	3x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD	3x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
Hard disk Group#2	N/A	N/A	N/A
RAID Controller	PERC H755 with front load bracket	PERC H755 for 2.5" x24 SAS/SATA chassis	PERC H755 with rear load bracket
Optical Drive	8X DVD-ROM, USB, External	8X DVD-ROM, USB, External	8X DVD-ROM, USB, External
Power Supply	Dual, Hot-plug, Power Supply Fault Tolerant Redundant (1+1), 800W, Mixed Mode	Dual, Hot-Plug, Fully Redundant Power Supply (1+1), 1400W, Mixed Mode	Dual, Hot-Plug, Fully Redundant Power Supply (1+1), 1400W, Mixed Mode
System Management	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced
Warranty	3Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 3Yr Keep Your Hard Drive	5Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive	5Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive
SRP (inc. VAT)	143,649	240,373	285,311



Dell PowerEdge R750

DEL-SNSR750C

Form Factor	2U, 2.5" Chassis with up to 16 Hot Plug Hard Drives, Trusted Platform Module 2.0 V3, + LCD Bezel + Half Length, Low Profile, 5 x16 + 1 x4 slots, ReadyRails Sliding Rails with Cable Management Arm
Processor	2 x Intel® Xeon® Silver 4314
Processor Speed / Core	2.4G, 16C/32T, 10.4GT/s, 24M Cache, Turbo, HT (135W) DDR4-2666
Memory	64GB (2x 32GB) RDIMM, 3200MT/s, Dual Rank, 16Gb BASE
Network	2x 1Gb LOM + Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0
Hard disk Group#1	4x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
Hard disk Group#2	N/A
RAID Controller	PERC H755 with rear load bracket
Optical Drive	No Internal Optical Drive
Power Supply	Dual, Hot-Plug, Fully Redundant Power Supply (1+1), 1100W, Mixed Mode
System Management	iDRAC9 Datacenter 15G with OpenManage Enterprise Advanced
Warranty	5Yr ProSupport & Mission Critical: (7x24) 4-hour Onsite Service + 5Yr Keep Your Hard Drive
SRP (inc. VAT)	255,570

LENOVO : ICT 66 TOWER

Lenovo

เครื่องคอมพิวเตอร์แม่ข่าย แบบที่ 1 จบ 130,000.-

	 CPU Gen3 ThinkSystem ST650 V2 LNV-7Z74S2FH00	 CPU Gen3-SSD ThinkSystem ST650 V2 LNV-7Z74S1X700
Form Factor	Intel Xeon Silver 4310T 10C 105W 2.3GHz Processor,Cache Memory 15MB x 1	Intel Xeon Silver 4310T 10C 105W 2.3GHz Processor,Cache Memory 15MB x 1
CPU	ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 1	ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 1
Memory	ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1	ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1
RAID Controller	ThinkSystem 2.5" 1.2TB 10K SAS 12Gb Hot Swap 512n HDD x 2	ThinkSystem 2.5" Multi Vendor 960GB Entry SATA 6Gb Hot Swap SSD x 2
Harddisk	ThinkSystem Broadcom 5720 1GbE RJ45 2-Port PCIe Ethernet Adapter x 1	ThinkSystem Broadcom 5720 1GbE RJ45 2-Port PCIe Ethernet Adapter x 1
NIC	ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2	ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2
Power Supply	XClarity Controller Enterprise	XClarity Controller Enterprise
System Management	3Yr. 24x7 warranty	3Yr. 24x7 warranty
Warranty	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
Included	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
SRP (inc. VAT)	148,600	151,600

เครื่องคอมพิวเตอร์แม่ข่าย แบบที่ 2 จบ 350,000.-

	 CPU Gen3 ThinkSystem ST650 V2 LNV-7Z74S2FG00	 CPU Gen3-SSD ThinkSystem ST650 V2 LNV-7Z74S2FJ00
Form Factor	Tower	Tower
CPU	Intel Xeon Gold 6326 16C 185W 2.9GHz Processor,Cache Memory 24MB x 2	Intel Xeon Gold 6326 16C 185W 2.9GHz Processor,Cache Memory 24MB x 2
CPU	ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 2	ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 2
Memory	ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1	ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1
RAID Controller	ThinkSystem 2.5" 2.4TB 10K SAS 12Gb Hot Swap 512e HDD x 4	ThinkSystem 2.5" Multi Vendor 960GB Entry SATA 6Gb Hot Swap SSD x 4
Harddisk	ThinkSystem Broadcom 57416 10GBASE-T 2-Port PCIe Ethernet Adapter x 1	ThinkSystem Broadcom 57416 10GBASE-T 2-Port PCIe Ethernet Adapter x 1
NIC	ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2	ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2
Power Supply	XClarity Controller Enterprise	XClarity Controller Enterprise
System Management	3Yr. 24x7 warranty	3Yr. 24x7 warranty
Warranty	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
Included	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
SRP (inc. VAT)	322,000	305,000

LENOVO : ICT 66 Rack -CPU AMD

เครื่องคอมพิวเตอร์แม่ข่าย แบบที่ 1 จบ 130,000.-

	 HDD ThinkSystem SR635 LNV-7Y99S64400	 SSD ThinkSystem SR635 LNV-7Y99S64300
Form Factor	Rack 1U	Rack 1U
CPU	ThinkSystem AMD EPYC 7272 12C 120W 2.9GHz Processor, Cache Memory 64MB x 1	ThinkSystem AMD EPYC 7272 12C 120W 2.9GHz Processor,Cache Memory 64MB x 1
CPU	ThinkSystem 16GB TruDDR4 2933MHz (1Rx4 1.2V) RDIMM-A x 1	ThinkSystem 16GB TruDDR4 2933MHz (1Rx4 1.2V) RDIMM-A x 1
Memory	ThinkSystem RAID 530-8i PCIe 12Gb Adapter x 1	ThinkSystem RAID 530-8i PCIe 12Gb Adapter x 1
RAID Controller	ThinkSystem 2.5" 1.2TB 10K SAS 12Gb Hot Swap 512n HDD x 2	ThinkSystem 2.5" MultiVendor 960GB Entry SATA 6Gb Hot Swap SSD x 2
Harddisk	ThinkSystem Broadcom 5720 1GbE RJ45 2-Port PCIe Ethernet Adapter x 1	ThinkSystem Broadcom 5720 1GbE RJ45 2-Port PCIe Ethernet Adapter x 1
NIC	ThinkSystem 750W(230/115V) Platinum Hot-Swap Power Supply x 2	ThinkSystem 750W(230/115V) Platinum Hot-Swap Power Supply x 2
Power Supply	XClarity Controller Enterprise	XClarity Controller Enterprise
System Management	3Yr. 24x7 warranty	3Yr. 24x7 warranty
Warranty	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
Included	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
SRP (inc. VAT)	124,900	117,900

เครื่องคอมพิวเตอร์แม่ข่าย แบบที่ 2 จบ 350,000.-

	 HDD ThinkSystem SR645 LNV-7D2XS7UK00	 SSD ThinkSystem SR645 LNV-7D2XS7UL00
Form Factor	Rack 1U	Rack 1U
CPU	ThinkSystem AMD EPYC 7313 16C 155W 3.0GHz Processor, Cache Memory 128MB x 2	ThinkSystem AMD EPYC 7313 16C 155W 3.0GHz Processor, Cache Memory 128MB x 2
CPU	ThinkSystem 16GB TruDDR4 3200MHz (2Rx8 1.2V) RDIMM-A x 2	ThinkSystem 16GB TruDDR4 3200MHz (2Rx8 1.2V) RDIMM-A x 2
Memory	ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1	ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1
RAID Controller	ThinkSystem 2.5" 2.4TB 10K SAS 12Gb Hot Swap 512e HDD v2 x 4	ThinkSystem 2.5" Multi Vendor 960GB Entry SATA 6Gb Hot Swap SSD x 4
Harddisk	ThinkSystem Broadcom 57416 10GBASE-T 2-port OCP Ethernet Adapter x 1	ThinkSystem Broadcom 57416 10GBASE-T 2-port OCP Ethernet Adapter x 1
NIC	ThinkSystem 750W (230/115V) V2 Platinum Hot-Swap Power Supply x 2	ThinkSystem 750W (230/115V) V2 Platinum Hot-Swap Power Supply x 2
Power Supply	XClarity Controller Enterprise	XClarity Controller Enterprise
System Management	3Yr. 24x7 warranty	3Yr. 24x7 warranty
Warranty	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
Included	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
SRP (inc. VAT)	234,200	237,800



SIS Distribution (Thailand) Public Company Limited
TEL. 02-020-3000
Email address : sis@sisthai.com

บริษัทขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว

ICT 66 Rack -CPU Intel



เครื่องคอมพิวเตอร์แม่ข่าย แบบที่ 1 จบ 130,000.-

 ThinkSystem SR630 V2 LNV-7Z71SSPT00		 ThinkSystem SR650 V2 LNV-7Z73TXPN00	
Form Factor	Rack 1U		Rack 2U
CPU	Intel Xeon Silver 4310T 10C 105W 2.3GHz Processor,Cache Memory 15MB x 1		Intel Xeon Silver 4310T 10C 105W 2.3GHz Processor,Cache Memory 15MB x 1
Memory	ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 1		ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 1
RAID Controller	ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1		ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1
Harddisk	ThinkSystem 2.5" 1.2TB 10K SAS 12Gb Hot Swap 512n HDD x 2		ThinkSystem 2.5" 1.2TB 10K SAS 12Gb Hot Swap 512n HDD x 2
NIC	ThinkSystem Broadcom 5720 1GbE RJ45 2-Port PCIe Ethernet Adapter x 1		ThinkSystem Broadcom 5720 1GbE RJ45 2-Port PCIe Ethernet Adapter x 1
Power Supply	ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2		ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2
System Management	XClarity Controller Enterprise		XClarity Controller Enterprise
Warranty	3Yr. 24x7 warranty		3Yr. 24x7 warranty
Included	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2		2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
SRP (inc. VAT)	137,000		149,800

 ThinkSystem SR630 V2 LNV-7Z71SSPR00		 ThinkSystem SR650 V2 LNV-7Z73TWKM00	
Form Factor	Rack 1U		Rack 2U
CPU	Intel Xeon Silver 4310T 10C 105W 2.3GHz Processor,Cache Memory 15MB x 1		Intel Xeon Silver 4310T 10C 105W 2.3GHz Processor,Cache Memory 15MB x 1
Memory	ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 1		ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 1
RAID Controller	ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1		ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1
Harddisk	ThinkSystem 2.5" Multi Vendor 960GB Entry SATA 6Gb Hot Swap SSD x 2		ThinkSystem 2.5" Multi Vendor 960GB Entry SATA 6Gb Hot Swap SSD x 2
NIC	ThinkSystem Broadcom 5720 1GbE RJ45 2-Port PCIe Ethernet Adapter x 1		ThinkSystem Broadcom 5720 1GbE RJ45 2-Port PCIe Ethernet Adapter x 1
Power Supply	ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2		ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2
System Management	XClarity Controller Enterprise		XClarity Controller Enterprise
Warranty	3Yr. 24x7 warranty		3Yr. 24x7 warranty
Included	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2		2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
SRP (inc. VAT)	156,000		132,000

เครื่องคอมพิวเตอร์แม่ข่าย แบบที่ 2 จบ 350,000.-

 ThinkSystem SR630 V2 LNV-7Z71SSPS00		 ThinkSystem SR650 V2 LNV-7Z73TXPL00	
Form Factor	Rack 1U		Rack 2U
CPU	Intel Xeon Gold 6326 16C 185W 2.9GHz Processor,Cache Memory 24MB x 2		Intel Xeon Gold 6326 16C 185W 2.9GHz Processor,Cache Memory 24MB x 2
Memory	ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 2		ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 2
RAID Controller	ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1		ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1
Harddisk	ThinkSystem 2.5" 2.4TB 10K SAS 12Gb Hot Swap 512e HDD v2 x 4		ThinkSystem 2.5" 2.4TB 10K SAS 12Gb Hot Swap 512e HDD x 4
NIC	ThinkSystem Broadcom 57416 10GBASE-T 2-port OCP Ethernet Adapter x 1		ThinkSystem Broadcom 57416 10GBASE-T 2-port OCP Ethernet Adapter x 1
Power Supply	ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2		ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2
System Management	XClarity Controller Enterprise		XClarity Controller Enterprise
Warranty	3Yr. 24x7 warranty		3Yr. 24x7 warranty
Included	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2		2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
SRP (inc. VAT)	288,700		296,700

 ThinkSystem SR630 V2 LNV-7Z71SSPQ00		 ThinkSystem SR650 V2 LNV-7Z73TXPM00	
Form Factor	Rack 1U		Rack 2U
CPU	Intel Xeon Gold 6326 16C 185W 2.9GHz Processor,Cache Memory 24MB x 2		Intel Xeon Gold 6326 16C 185W 2.9GHz Processor,Cache Memory 24MB x 2
Memory	ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 2		ThinkSystem 16GB TruDDR4 3200 MHz (2Rx8 1.2V) RDIMM x 2
RAID Controller	ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1		ThinkSystem RAID 5350-8i PCIe 12Gb Adapter x 1
Harddisk	ThinkSystem 2.5" Multi Vendor 960GB Entry SATA 6Gb Hot Swap SSD x 4		ThinkSystem 2.5" Multi Vendor 960GB Entry SATA 6Gb Hot Swap SSD x 4
NIC	ThinkSystem Broadcom 57416 10GBASE-T 2-port OCP Ethernet Adapter x 1		ThinkSystem Broadcom 57416 10GBASE-T 2-port OCP Ethernet Adapter x 1
Power Supply	ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2		ThinkSystem V2 750W(230V/115V) Platinum Hot-Swap Power Supply v2 x 2
System Management	XClarity Controller Enterprise		XClarity Controller Enterprise
Warranty	3Yr. 24x7 warranty		3Yr. 24x7 warranty
Included	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2		2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord (90Y3016) x 2
SRP (inc. VAT)	284,550		291,750

HPE : Rack Servers



HPE ProLiant DL160 Gen10 4210R
HPE-P35516-B21

HPE DL160G10 Xeon 4214R
HPE-P35518-B21

CPU Types	Intel Xeon-Silver 4210R (2.4GHz/10-core/100W)	Intel Xeon-Silver 4214R (2.4GHz/12-core/100W)
CPU Min., max	1 Processors (up to 2)	1 Processors (up to 2)
CPU L3 Cache	13.75 MB	16.5 MB
Memory	16 GB RDIMM DDR4 2933 MT/s	16 GB RDIMM DDR4 2933 MT/s
Graphic	Integrated Video Standard	Integrated Video Standard
PCI Slot	2 PCIe 3.0 slots	2 PCIe 3.0 slots
Harddisk	8 SFF Chassis	8 SFF Chassis
RAID Controller	HPE Smart Array S100i SR Gen10 SW RAID - SATA only Support OS Windows Server only	HPE Smart Array S100i SR Gen10 SW RAID - SATA only Support OS Windows Server only
Optical Drive	None ship as standard	None ship as standard
Total, Hotswap	8 SFF HDD Bays	8 SFF HDD Bays
Max, Internal disks	8 SFF Chassis	8 SFF Chassis
Interfaces	1 Rear VGA Port - Standard	1 Rear VGA Port - Standard
Onboard Gigabit Ethernet	Embedded 2-port 1GbE	Embedded 2-port 1GbE
Power Supply	1x 500W Flex Slot Platinum Hot Plug Power Supply (up to 2)	1x 500W Flex Slot Platinum Hot Plug Power Supply (up to 2)
Form Factor	rack 1U	rack 1U
OS Support	Microsoft Windows Server	Microsoft Windows Server
Warranty	HPE 3Y TC Ess DL160 Gen10 SVC	3-year parts, 3-year labor, 3-year onsite support with next business day response
Add On	Harddisk HPE 480GB SATA MU SFF BC MV SSD x 3 unit Power Supply HPE 500W FS Plat Ht Plg LH Pwr Sply Kit Warranty HPE 3Y TC Ess DL160 Gen10 SVC	Harddisk HPE 480GB SATA MU SFF BC MV SSD x 3 unit Power Supply HPE 500W FS Plat Ht Plg LH Pwr Sply Kit Warranty HPE 3Y TC Ess DL160 Gen10 SVC
SRP (inc. VAT)	143,900.-	156,540.-



HPE ProLiant DL320 Gen11 4410Y
HPE-P57687-B21

HPE ProLiant DL360 Gen10 4210
KIT-DL360G10CLX02

CPU Types	Intel Xeon 4410Y (12-Core, 2.0 GHz, 150W)	Intel Xeon-Silver 4210 (10 core, 2.2 GHz, 85W)
CPU Min., max	1 Processors (Support 1 CPU)	1 Processors (up to 2)
CPU L3 Cache	30 MB	13.75 MB
Memory	16 GB UDIMM DDR5; 4800 MT/s (1x 16GB)	16 GB RDIMM DDR4 2R 2933 MT/s
Graphic	Integrated Video Standard	Integrated Video Standard
PCI Slot	2 x16 FHHL PCIe Gen5	2 PCIe 3.0 slots
Harddisk	8 SFF Chassis	HPE 480GB SATA 6G Mixed Use SFF SC Multi Vendor SSD x 3 Unit
RAID Controller	MR408i-o with Megacell Battery	HPE Smart Array P408i-a SR /2GB (Support RAID 0, 1, 5, 6, 10, 50, 60, 1 ADM, 10 ADM)
Optical Drive	None ship as standard	None ship as standard
Total, Hotswap	8 SFF HDD Bays	8 SFF HDD Bays
Max, Internal disks	8 SFF Chassis	8 SFF Chassis
Interfaces	1 Rear VGA Port - Standard	1 Rear VGA Port - Standard
Onboard Gigabit Ethernet	HPE embedded 2-port 1 GbE Ethernet adapter	HPE Ethernet 1Gb 4-port FLR-T I350-T4V2
Power Supply	1x 500W Flex Slot Platinum Hot Plug Power Supply (up to 2)	1x 500W Flex Slot Platinum Hot Plug Power Supply (up to 2)
Form Factor	rack 1U	rack 1U
OS Support	Microsoft Windows Server	Microsoft Windows Server, Red Hat Enterprise Linux (RHEL) SUSE Linux Enterprise Server (SLES)
Warranty	3-year parts, 3-year labor, 3-year onsite support with next business day response	3-year parts, 3-year labor, 3-year onsite support with next business day response
Add On	Harddisk HPE 480GB SATA RI SFF BC MV SSD x 3 unit Bezel HPE DL3XX Gen11 1U Bezel Kit Power Supply HPE 500W FS Plat Ht Plg LH Pwr Sply Kit Warranty HPE 3 Year Tech Care Essential DL320 Gen11 HW Service (24x7)	
SRP (inc. VAT)	171,900.-	122,900.-

HPE : Rack Servers



HPE ProLiant DL360 Gen10 Plus 4309Y

HPE-P35516-B21



HPE ProLiant DL380 Gen10 4210R

HPE-P24841-B21

CPU Types	Intel Xeon 4309Y (8-Core, 2.8 GHz, 105W)	Intel Xeon-Silver 4210R (2.4GHz, 10 core, 100W)
CPU Min., max	1 Processors (up to 2)	1 Processors (up to 2)
CPU L3 Cache	12 MB	13.75 MB
Memory	32 GB RDIMM 2R 3200 MT/s (1x 32 GB)	32 GB RDIMM 2R 2933 MT/s (1x 32 GB)
Graphic	Integrated Video Standard	Integrated Video Standard
PCI Slot	2 PCIe 3.0 slots	3 PCIe: x8/x16/x8
Harddisk		None ship as standard
RAID Controller	MR416i-a/4GB with Smart Storage Battery (Support RAID 0, 1, 5, 6, 10, 50, 60, 1 ADM, 10 ADM)	MR416i-p/4GB with Smart Storage Battery (Support RAID 0, 1, 5, 6, 10, 50, 60, 1 ADM, 10 ADM)
Optical Drive	None ship as standard	None ship as standard
Total, Hotswap	8 SFF HDD Bays	8 SFF HDD Bays
Max, Internal disks	8 SFF Chassis	8 SFF Chassis
Interfaces	1 Rear VGA Port - Standard	1 Rear VGA Port - Standard
Onboard Gigabit Ethernet	HPE Ethernet 1Gb 4-port FLR-T I350-T4V2	HPE Ethernet 1Gb 4-port FLR-T I350-T4V2
Power Supply	1x 500W Flex Slot Platinum Hot Plug Power Supply (up to 2)	1x 800W Flex Slot Platinum Hot Plug Power Supply (up to 2)
Form Factor	rack 1U	rack 2U
OS Support	"Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)""	"Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)""
Warranty	3-year parts, 3-year labor, 3-year onsite support with next business day response	3-year parts, 3-year labor, 3-year onsite support with next business day response
Add On	Harddisk HPE 480GB SATA MU SFF BC MV SSD x 3 unit Network BCM 5719 1Gb 4p BASE-T Adptr Bezel HPE Gen10 2U Bezel Kit x 1 unti Power Supply HPE 800W FS Plat Ht Plg LH PS Kit x1 Warranty HPE 3Y TC Ess DL380G10+ SVC (24x7)	HPE 960GB SATA 6G Mixed Use SFF SC Multi Vendor SSD x 3 unit HPE Gen10 2U Bezel Kit x 1 unti HPE 800W FS Plat Ht Plg LH PS Kit x1 HPE 3Y TC Ess DL380G10+ SVC (24x7)
SRP (inc. VAT)	233,900.-	214,000.-



HPE ProLiant DL380 Gen10 Plus 4309Y

HPE-P55245-B21



HPE ProLiant DL380 Gen10 Plus 4310

HPE-P55246-B21

CPU Types	Intel Xeon 4309Y (8-Core, 2.8 GHz, 105W)	Intel Xeon 4310 (12-Core, 2.1 GHz, 120W)
CPU Min., max	1 Processors (up to 2)	1 Processors (up to 2)
CPU L3 Cache	12MB	18MB
Memory	32 GB RDIMM 2R 3200 MT/s (1x 32 GB)	32 GB RDIMM 2R 3200 MT/s (1x 32 GB)
Graphic	Integrated Video Standard	Integrated Video Standard
PCI Slot	3 PCIe: x8/x16/x8	3 PCIe: x8/x16/x8
Harddisk	None ship as standard	None ship as standard
RAID Controller	MR416i-p/4GB with Smart Storage Battery (Support RAID 0, 1, 5, 6, 10, 50, 60, 1 ADM, 10 ADM)	MR416i-p/4GB with Smart Storage Battery (Support RAID 0, 1, 5, 6, 10, 50, 60, 1 ADM, 10 ADM)
Optical Drive	None ship as standard	None ship as standard
Total, Hotswap	8 SFF HDD Bays	8 SFF HDD Bays
Max, Internal disks	8 SFF Chassis	8 SFF Chassis
Interfaces	1 Rear VGA Port - Standard	1 Rear VGA Port - Standard
Onboard Gigabit Ethernet	HPE Ethernet 1Gb 4-port FLR-T I350-T4V2	HPE Ethernet 1Gb 4-port FLR-T I350-T4V2
Power Supply	1x 800W Flex Slot Platinum Hot Plug Power Supply (up to 2)	1x 800W Flex Slot Platinum Hot Plug Power Supply (up to 2)
Form Factor	rack 2U	rack 2U
OS Support	"Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)""	"Microsoft Windows Server Red Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)""
Warranty	3-year parts, 3-year labor, 3-year onsite support with next business day response	3-year parts, 3-year labor, 3-year onsite support with next business day response
Add On	Harddisk HPE 480GB SATA MU SFF BC MV SSD x 3 unit Network BCM 5719 1Gb 4p BASE-T Adptr Bezel HPE Gen10 2U Bezel Kit x 1 unti Power Supply HPE 800W FS Plat Ht Plg LH PS Kit x1 Warranty HPE 3Y TC Ess DL380G10+ SVC (24x7)	Harddisk HPE 480GB SATA MU SFF BC MV SSD x 3 unit Network BCM 5719 1Gb 4p BASE-T Adptr Bezel HPE Gen10 2U Bezel Kit x 1 unti Power Supply HPE 800W FS Plat Ht Plg LH PS Kit x1 Warranty HPE 3Y TC Ess DL380G10+ SVC (24x7)
SRP (inc. VAT)	227,900.-	227,900.-



SIS Distribution (Thailand) Public Company Limited
TEL. 02-020-3000
Email address : sis@sisthai.com

บริษัทฯ ขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว