

CREALITY : 3D Printer


CREALITY



| Model | CR-10 Max | CR-10 Smart | CR-30 |
|------------------|---|---------------------------------|--|
| Molding Tech | FDM (Fused Deposition Molding) | FDM (Fused Deposition Molding) | FDM (Fused Deposition Molding) |
| Filament | PLA | PLA / ABS / TPU / PETTG | PLA / TPU / PETG |
| Hotbed Temp | ≤100 C | ≤100 C | ≤100 C |
| File Tranfer | TF Card/USB | SD Card / Wifi | USB / SD Card |
| Language | English / Chinese | 9 language | Chinese / English |
| File Format | STL/OBJ/AMF | STL/OBJ/AMF | STL/OBJ/AMF |
| Slice Software | Creality Slicer / Cura / Repetier - Host / Simplify3D | Creality / Cura | CrealityBelt |
| Operation System | Window XP / 7 / 8 / 10 Mac / Linux | | 0.1mm - 0.4mm |
| Power Supply | RV : 100 - 240 V , Output : 24V | RV : 100 - 240 V , Output : 24V | RV: 100-120V / 200-240V , Output : 24V |
| Nominal Power | 750W | 1.75 mm | 1.75mm |
| Machine Size | 650 x 785 x 735 mm 20 Kg | 578 x 522 x 648 mm 14 Kg | 535 x 656 x 410 mm 16.5 Kg |
| SRP(inc.VAT) | 33,990.- | 16,290.- | 46,590.- |



| Model | CR-200B | CR-3040 Pro | Ender 3 Max |
|------------------|---|---|---|
| Molding Tech | FDM (Fused Deposition Molding) | FDM (Fused Deposition Molding) | FDM (Fused Deposition Molding) |
| Filament | PLA / ABS | PLA / ABS | PLA / PETG / ABS |
| Hotbed Temp | ≤100 C | ≤100 C | ≤100 C |
| File Tranfer | USB / SD Card | USB / SD Card | TF Card / USB |
| Language | Chinese / English | Chinese / English | Chinese / English |
| File Format | STL/OBJ/AMF | STL/OBJ/AMF | STL / OBJ / AMF |
| Slice Software | Creality Slicer / Cura / Repetier - Host / Simplify3D | Creality Slicer / Cura / Repetier - Host / Simplify3D | Creality Slicer / Cura / Repetier - Host / Simplify3D |
| Operation System | WIN / XP / MAC / Linux / Vista | WIN / XP / MAC / Linux / Vista | WIN / XP / MAC / Linux / Vista |
| Power Supply | RV : 115 - 235V . Out put : 24V | RV : 115 - 230 V , Output : 24V | Rated Voltage : 115V - 230V Output : 24V |
| Nominal Power | 350W | 500W | 350W |
| Machine Size | 411 x 435 x 503 mm 16 Kg | 580 x 471 x 885 mm 58 Kg | 513 x 563 x 590 mm 9.5 Kg |
| SRP(inc.VAT) | 16,290.- | 64,590.- | 11,890.- |



| Model | Ender 3 V2 | Ender 3 |
|------------------|---|---|
| Molding Tech | FDM (Fused Deposition Molding) | FDM (Fused Deposition Molding) |
| Filament | PLA / PETG / ABS / TPU | PLA / TPU / Wood / Carbon Fiber , etc. |
| Hotbed Temp | ≤100 C | ≤100 C |
| File Tranfer | USB / TF Card | USB / TF Card |
| Language | Chinese / English | Chinese / English |
| File Format | STL / OBJ / AMF | STL / OBJ / AMF |
| Slice Software | Creality Slicer / Cura / Repetier - Host / Simplify3D | Creality Slicer / Cura / Repetier - Host / Simplify3D |
| Operation System | WIN / XP / MAC / Linux / Vista | WIN / XP / MAC / Linux / Vista |
| Power Supply | RV : 115 / 230V Output 24V | RV : 115 / 230V Output 24V |
| Nominal Power | 350W | 270W |
| Machine Size | 475 x 470 x 473 mm 7.8 Kg | 440 x 440 x 465 mm 6.62 Kg |
| SRP(inc.VAT) | 9,890.- | 6,490.- |





SIS Distribution (Thailand) Public Company Limited
TEL. 02-020-3000
Email address : sis@sisthai.com

บริษัทฯ ขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แลว

CREALITY : 3D Printer

CREALITY


 Layer Thickness
0.1mm - 0.6mm


| Model | Ender-7 | K8 | Sermoon D1 |
|------------------|---|--|---|
| Molding Tech | FDM (Fused Deposition Molding) | FDM (Fused Deposition Molding) | FDM (Fused Deposition Molding) |
| Filament | PLA / PETG / ABS | Light - Transmitting / Shading Material (Filament) | PLA / ABS / TPU |
| Hotbed Temp | ≤100 C | ≤65 C | ≤100 C |
| File Transfer | USB Cable / TF Card | USB / SD Card | Online or SD Card |
| Language | CH / EN / Spanish / German / French / Russian | Chinese | Chinese / English |
| File Format | STL / OBJ / AMF | STL / OBJ / AMF | STL / OBJ / AMF |
| Slice Software | Creality Slicer / Cura / Repetier - Host / Simplify3D | | Creality Slicer / Cura / Repetier - Host / Simplify3D |
| Operation System | Windows XP / Vista / 7 / 10 MAC Linux | Win 7 / Win 10 64 bits | WIN / XP / MAC / Linux / Vista |
| Power Supply | RV100 - 120V / 200 - 240V Output 24V | RV : 100 -240V , Output 24V | AC 100 - 240V , DC 24V |
| Nominal Power | 350W | 1.8KW | |
| Machine Size | 430 x 460 x 570 mm 17.2 Kg | 1222 x 1130 x 700 mm 65 Kg | 500 x 500 x 531 mm 20.5 Kg |
| SRP(inc.VAT) | 24,790.- | 112,000.- | 26,490.- |



| Model | Halot Sky |
|---------------------|--|
| Molding Tech | LCD resin Curing |
| Filament | 405 mm Photosensitive Resin |
| Print Speed | 1 - 4 / s layer |
| Operation interface | Support 12 Language (Chinese / English preferred) |
| XY - Axis Precision | 0.05 mm |
| Layer Thickness | 0.01 - 0.2 mm |
| Display Screen | 5 - inch Full - Color Touch Screen |
| Light Source | Integrate light Source |
| Z - Axis Type | Dual linear Guid Rails + Ball Screws |
| Trough | Compatible with LD - 006 Trough |
| Machine Size | 340 x 202 x 552 mm 16.5 Kg |
| SRP(inc.VAT) | 38,790.- |



| Model | Halot one |
|---------------------|--|
| Molding Tech | LCD resin Curing |
| Print Filament | Photosensitive Resin |
| Print Precision | 1 - 4 / s layer |
| Print Method | Chinese / English |
| Operation interface | 405 mm |
| Supported Formant | 5.0 Capacitive layer |
| Print Speed | 0.051 mm |
| Operation System | Windows 7 and above |
| Power Requirement | Rated Voltage : 100 - 240V , Output : 24V |
| Rated Power | 100W |
| Machine Size | 221 x 221 x 494 mm 7.1 Kg |
| SRP(inc.VAT) | 9,890.- |

3D PRINTER

137

เครื่องฟอกชิ้นงาน



| Model | UW - 02 |
|--------------------|--------------------------------|
| Washing and Curing | 2 / 5 / 10 / 15 / 20 / 30 mins |
| Machine Function | Washing and Curing |
| Speed | Regular / Fast |
| Power Requirement | RV : 100 -240V , Output 24V |
| Rated Power | 60W |
| Supported language | Chinese / English |
| Operation System | Windows 7 and above |
| Washing Basket | 304 Stainless Steel |
| Curing Platform | Mirror Stainless Steel |
| Machine Size | 325 x 295 x 485 mm 9 Kg |
| SRP(inc.VAT) | 7,490.- |


 SIS Distribution (Thailand) Public Company Limited
 TEL. 02-020-3000
 Email address : sis@sis-thai.com

 ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว
 บริษัทขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

CREALITY : Spare Part**CREALITY**

| SIS Part No. | Creality | SRP (Inc.VAT) |
|----------------|--|---------------|
| CLT-4008050016 | CR Scan 01 upgraded | 27,750 |
| CLT-4001050011 | Ender-3 Screen Kit | 513 |
| CLT-4004090015 | Platform Sticker | 205 |
| CLT-4004070007 | Thermistor Cable | 52 |
| CLT-4001010005 | Auto Leveling Sensor 8 Bit/BL Touch | 1,947 |
| CLT-4001040003 | Hotbed Kit | 533 |
| CLT-4001070002 | Pulley Kit | 72 |
| CLT-4001080033 | Ender-3 Y Axis Timing Belt Kit | 72 |
| CLT-4004090035 | Carborundum platform glass board | 287 |
| CLT-4004090014 | Carborundum Glass Platform 310x320 | 462 |
| CLT-4001040002 | Hotbed kit | 1,128 |
| CLT-4001050009 | Ender-3 Max Screen Kit | 1,107 |
| CLT-4004090031 | Carborundum Glass Platform Ender-3V2 | 287 |
| CLT-4004180004 | Limit Switch Kit | 63 |
| CLT-4002020012 | Ender-3 V2 Slient Motherboard | 1,640 |
| CLT-4003010006 | Dual Screw Upgrade Package | 1,177 |
| CLT-4004070012 | Thermistor Kit | 72 |
| CLT-4001040019 | Hotbed Kit Ender 3 V2 235x235 | 564 |
| CLT-4001010009 | End-3V2 BL Touch Auto Leveling Kit 32Bit | 1,721 |
| CLT-4001070004 | Pulley Kit | 205 |
| CLT-4004010063 | Memory card | 257 |
| CLT-4001040025 | Hotbed Plate Kit | 1,282 |
| CLT-4004070004 | Thermistor | 42 |
| CLT-4001080023 | Timing Belt Kit L 1220mm Ender 5 Plus | 94 |
| CLT-4001050037 | Screen Kit | 2,357 |
| CLT-4001040039 | Hotbed Kit | 2,868 |
| CLT-4001090010 | Filament Sensor Kit | 257 |
| CLT-4001050008 | Screen Kit | 1,004 |
| CLT-4001040001 | Platform Kit | 3,278 |
| CLT-4004070009 | NTC | 52 |
| CLT-4004010129 | CR-30 Belt Kit | 2,562 |
| CLT-4001040015 | Hotbed Board Kit | 1,895 |
| CLT-4004070001 | Nozzle Thermistor | 52 |
| CLT-4001050036 | Screen Kit | 2,050 |
| CLT-4001090010 | Filament Sensor Kit | 226 |
| CLT-4004090065 | Carborundum Glass Platform Board | 410 |
| CLT-4001090010 | Filament Sensor Kit | 257 |
| CLT-4001050017 | Screen | 1,282 |
| CLT-4001040024 | Hotbed Kit | 1,282 |
| CLT-4004090045 | CR-200B carborundum glass plate | 329 |
| CLT-4004070015 | Thermistor | 63 |
| CLT-4004120012 | Synchronous Wheel Kit | 124 |
| CLT-4004180016 | limit switch Module | 33 |
| CLT-4001090010 | Filament Sensor Kit | 257 |
| CLT-4001050024 | Display screen | 2,357 |
| CLT-4001040026 | Hotbed Board Kit | 1,128 |
| CLT-4004090059 | Carborundum Glass Platform | 462 |
| CLT-4004070019 | Thermistor | 42 |
| CLT-4004090059 | Carborundum Glass Platform | 410 |
| CLT-4004010071 | Resin Vat Kit | 1,434 |
| CLT-4001050038 | Touch Screen Kit | 1,741 |
| CLT-4004010002 | Air Filter Fan Cover | 103 |

CREALITY : Consumable**CREALITY**

| SIS Part No. | Creality | SRP (Inc.VAT) |
|----------------|---------------------------------|---------------|
| CLT-3301010040 | HP-PLA White 1.75mm 1KG | 646 |
| CLT-3301010041 | HP-PLA Black 1.75mm 1KG | 646 |
| CLT-3301010039 | HP-PLA Grey 1.75mm 1KG | 646 |
| CLT-3301010034 | HP-PLA Orange 1.75mm 1KG | 646 |
| CLT-3301010038 | HP-PLA Red 1.75mm 1KG | 646 |
| CLT-3301010036 | HP-PLA Yellow 1.75mm 1KG | 646 |
| CLT-3301010037 | HP-PLA Blue 1.75mm 1KG | 646 |
| CLT-3301010035 | HP-PLA Green 1.75mm 1KG | 646 |
| CLT-3301010061 | CR-PLA Black 1.75mm 1KG | 636 |
| CLT-3301010066 | CR-PLA Grey 1.75mm 1KG | 636 |
| CLT-3301010024 | CR-PLA Sapphire blue 1.75mm 1KG | 636 |
| CLT-3301010120 | CR-PLA Grass Green 1.75mm 1KG | 636 |
| CLT-3301010069 | CR-PLA Orange 1.75mm 1KG | 636 |
| CLT-3301010068 | CR-PLA Pink 1.75mm 1KG | 636 |
| CLT-3301010062 | CR-PLA Red 1.75mm 1KG | 636 |
| CLT-3301010063 | CR-PLA Yellow 1.75mm 1KG | 636 |
| CLT-3301010121 | Ender-PLA White 1.75mm 1KG | 513 |
| CLT-3301010122 | Ender-PLA Black 1.75mm 1KG | 513 |
| CLT-3301010123 | Ender-PLA Grey 1.75mm 1KG | 513 |
| CLT-3301010124 | Ender-PLA Red 1.75mm 1KG | 513 |
| CLT-3301010126 | Ender-PLA Yellow 1.75mm 1KG | 513 |
| CLT-3301010125 | Ender-PLA Blue 1.75mm 1KG | 513 |
| CLT-3301020012 | CR-ABS White 1.75mm 1KG | 466 |
| CLT-3301020013 | CR-ABS Orange 1.75mm 1KG | 466 |
| CLT-3301020016 | CR-ABS Pink 1.75mm 1KG | 466 |
| CLT-3301020008 | CR-ABS Black 1.75mm 1KG | 466 |
| CLT-3301020014 | CR-ABS Red 1.75mm 1KG | 466 |
| CLT-3301020010 | CR-ABS Yellow 1.75mm 1KG | 466 |
| CLT-3301020007 | CR-ABS Grey 1.75mm 1KG | 466 |
| CLT-3301020011 | CR-ABS Blue 1.75mm 1KG | 466 |
| CLT-3301020009 | CR-ABS Green 1.75mm 1KG | 466 |
| CLT-3301020015 | CR-ABS Brown 1.75mm 1KG | 466 |
| CLT-3301040010 | CR-TPU White 1.75mm 1KG | 855 |



CREALITY : Consumable

CREALITY

| SIS Part No. | Creality | SRP (Inc.VAT) |
|----------------|--|---------------|
| CLT-3301040003 | CR-TPU Orange 1.75mm 1KG | 855 |
| CLT-3301040002 | CR-TPU Pink 1.75mm 1KG | 855 |
| CLT-3301040009 | CR-TPU Black 1.75mm 1KG | 855 |
| CLT-3301040008 | CR-TPU Red 1.75mm 1KG | 855 |
| CLT-3301040004 | CR-TPU Yellow 1.75mm 1KG | 855 |
| CLT-3301040005 | CR-TPU Grey 1.75mm 1KG | 855 |
| CLT-3301040011 | CR-TPU Blue 1.75mm 1KG | 855 |
| CLT-3301040006 | CR-TPU Green 1.75mm 1KG | 855 |
| CLT-3301040001 | CR-TPU Brown 1.75mm 1KG | 855 |
| CLT-3302010007 | Water Resin, 1kg, White, Alu Can | 1,434 |
| CLT-3302010008 | Water Resin, 1kg, Yellow, Alu Can | 1,434 |
| CLT-3302010009 | Water Resin, 1kg, Transp blue, Alu Can | 1,434 |
| CLT-3302010010 | Water Resin, 1kg, skin color, Alu Can | 1,434 |
| CLT-3302010011 | Water Resin, 1kg, grey, Alu Can | 1,434 |
| CLT-3302010012 | Water Resin, 1kg, black, Alu Can | 1,434 |
| CLT-3302010013 | Water Resin, 1kg, purple, Alu Can | 1,434 |
| CLT-3302010014 | Water Resin, 1kg, Transp, Alu Can | 1,434 |
| CLT-3302010015 | Water Resin, 1kg, Transp red, Alu Can | 1,434 |
| CLT-3302010016 | Water Resin, 1kg, Transp green, Alu Can | 1,434 |
| CLT-3302010001 | Water Resin, 500g, purple, Alu Can | 739 |
| CLT-3302010002 | Water Resin, 500g, transpaent, Alu Can | 739 |
| CLT-3302010017 | Water Resin, 500g, White, Alu Can | 739 |
| CLT-3302010020 | Water Resin, 500g, skin color, Alu Can | 739 |
| CLT-3302010021 | Water Resin, 500g, grey, Alu Can | 739 |
| CLT-3302010022 | Water Resin, 500g, black, Alu Can | 739 |
| CLT-3302010003 | Water Resin, 500g, Transp red, Alu Can | 739 |
| CLT-3302010004 | Water Resin, 500g, Transp green, Alu Can | 739 |
| CLT-3302010018 | Water Resin, 500g, Yellow, Alu Can | 739 |
| CLT-3302010019 | Water Resin, 500g, Transp blue, Alu Can | 739 |
| CLT-3302030009 | Low Odor Resin, 1kg, grey, Alu Can | 1,107 |
| CLT-3302030015 | Low Odor Resin, 1kg, Transp green, Alu Can | 1,107 |
| CLT-3302030016 | Low Odor Resin, 1kg, yellow, Alu Can | 1,107 |
| CLT-3302030017 | Low Odor Resin, 1kg, blue, Alu Can | 1,107 |
| CLT-3302030018 | Low Odor Resin, 1kg, black, Alu Can | 1,107 |
| CLT-3302030019 | Low Odor Resin, 1kg, orange, Alu Can | 1,107 |
| CLT-3302030020 | Low Odor Resin, 1kg, green, Alu Can | 1,107 |
| CLT-3302030021 | Low Odor Resin, 1kg, skin color, Alu Can | 1,107 |
| CLT-3302030022 | Low Odor Resin, 1kg, Transp, Alu Can | 1,107 |
| CLT-3302030023 | Low Odor Resin, 1kg, Transp red, Alu Can | 1,107 |
| CLT-3302030024 | Low Odor Resin, 1kg, red, Alu Can | 1,107 |
| CLT-3302030026 | Low Odor Resin, 1kg, White, Alu Can | 1,107 |
| CLT-3302030027 | Low Odor Resin, 1kg, Transp blue, Alu Can | 1,107 |
| CLT-3302030002 | Low Odor Resin, 500g, Transp, Alu Can | 555 |
| CLT-3302030003 | Low Odor Resin, 500g, skin, Alu Can | 555 |
| CLT-3302030012 | Low Odor Resin, 500g, Grey, Alu Can | 555 |
| CLT-3302030013 | Low Odor Resin, 500g, White, Alu Can | 555 |
| CLT-3302030001 | Low Odor Resin, 500g, Transp Red, Alu Can | 555 |
| CLT-3302030004 | Low Odor Resin, 500g, Green, Alu Can | 555 |
| CLT-3302030005 | Low Odor Resin, 500g, Orange, Alu Can | 555 |
| CLT-3302030006 | Low Odor Resin, 500g, Black, Alu Can | 555 |
| CLT-3302030007 | Low Odor Resin, 500g, Blue, Alu Can | 555 |
| CLT-3302030008 | Low Odor Resin, 500g, Yellow, Alu Can | 555 |
| CLT-3302030010 | Low Odor Resin, 500g, Transp Green, Alu Can | 555 |
| CLT-3302030011 | Low Odor Resin, 500g, Transp Blue, Alu Can | 555 |
| CLT-3302030025 | Low Odor Resin, 500g, Red, Alu Can | 555 |
| CLT-3302020053 | STD. Rigid Resin, 1kg, grey, Alu Can | 974 |
| CLT-3302020055 | STD. Rigid Resin, 1kg, black, Alu Can | 974 |
| CLT-3302020056 | STD. Rigid Resin, 1kg, Transp, Alu Can | 974 |
| CLT-3302020057 | STD. Rigid Resin, 1kg, skin, Alu Can | 974 |
| CLT-3302020059 | STD. Rigid Resin, 1kg, Transp Red, Alu Can | 974 |
| CLT-3302020060 | STD. Rigid Resin, 1kg, Transp Blue, Alu Can | 974 |
| CLT-3302020061 | STD. Rigid Resin, 1kg, Transp Green, Alu Can | 974 |



เส้นใยชนิดต่างๆ

1. พลาสติก PLA
 2. พลาสติก ABS
 3. พลาสติก TPU แบบยืดหยุ่น
- เป็นเส้นใยพลาสติกคุณภาพสูงที่สามารถย่อยสลายได้และไม่ก่อให้เกิดมลพิษ มาในลักษณะเป็นม้วน

| | |
|------------------------|------------------|
| Technical Date | CR - PLA |
| Diameter | 1.75 mm |
| Net Weight | 1 Kg |
| Printing Temp | 195 - 210 C |
| Bed | 45 - 55 C |
| Impact Strength | ≥ 3% |
| Tensile Strength | ≥ 60 Mpa |
| Specific Gravity | 1.25 ± 0.05g/cm3 |
| Solution Flow Velocity | 5 - 7 g/10 min |
| Hydroscopicity | 0.50% |



พลาสติก Resin

เป็นพลาสติกเหลวบรรจุขวด

High hardness with good toughness
High printing speed
Low shrinkage rate
Almost odorless and non - toxic
High hardness of 88D
Compatible with most LCD resin printer