



RAM : PC & Notebook

Limited lifetime warranty




JetRam Article	Description	Bus	CAS Latency	SRP (Inc VAT)
Jet Ram (JM Series) : Value RAM จุดขายคือราคาถูก เหมาะกับลูกค้าที่เน้นราคาเป็นหลัก				
	SO-DIMM (For Notebook)		U-DIMM (For PC)	
SO-DIMM (For Notebook)				
TCN-JM2666HSH-4G	4GB JM DDR4 2666Mhz SO-DIMM 1Rx8	2666	CL19	Call
TCN-JM2666HSB-8G	8GB JM DDR4 2666Mhz SO-DIMM 1Rx8			Call
TCN-JM2666HSG-8G	8GB JM DDR4 2666Mhz SO-DIMM 1Rx16			Call
TCN-JM2666HSB-16G	16GB JM DDR4 2666Mhz SO-DIMM 2Rx8			Call
TCN-JM2666HSE-16G	16GB JM DDR4 2666Mhz SO-DIMM 1Rx8			Call
TCN-JM2666HSE-32G	32GB JM DDR4 2666Mhz SO-DIMM 2Rx8			Call
TCN-JM3200HSH-4G	4GB JM DDR4 3200Mhz SO-DIMM 1Rx8 NEW!!	3200	CL22	Call
TCN-JM3200HSB-8G	8GB JM DDR4 3200Mhz SO-DIMM 1Rx8	3200	CL22	Call
TCN-JM3200HSG-8G	8GB JM DDR4 3200Mhz SO-DIMM 1Rx16 1Gx16 CL22 1.2V	3200	CL22	Call
TCN-JM3200HSE-16G	16GB JM DDR4 3200Mhz SO-DIMM 1Rx8		CL22	Call
TCN-JM3200HSE-32G	32GB JM DDR4 3200Mhz SO-DIMM 1Rx8 CL22	3200	CL22	Call
U-DIMM (For PC)				
TCN-JM2666HLH-4G	4GB JM DDR4 2666Mhz U-DIMM 1Rx8	2666	CL19	Call
TCN-JM2666HLB-8G	8GB JM DDR4 2666Mhz U-DIMM 1Rx8			Call
TCN-JM2666HLG-8G	8GB JM DDR4 2666Mhz U-DIMM 1Rx16			Call
TCN-JM2666HLB-16G	16GB JM DDR4 2666Mhz U-DIMM 2Rx8			Call
TCN-JM2666HLE-16G	16GB JM DDR4 2666Mhz U-DIMM 1Rx8			Call
TCN-JM2666HLE-32G	32GB JM DDR4 2666Mhz U-DIMM 2Rx8			Call
TCN-JM3200HLH-4G	4GB JM DDR4 3200Mhz U-DIMM 1Rx8 NEW!!	3200	CL22	Call
TCN-JM3200HLB-8G	8GB JM DDR4 3200Mhz U-DIMM 1Rx8	3200	CL22	Call
TCN-JM3200HLB-16GK	16GB KIT JM DDR4 3200Mhz U-DIMM 1Rx8 1Gx8 CL22 1.2V	3200	CL22	Call
TCN-JM3200HLE-16G	16GB JM DDR4 3200Mhz U-DIMM 1Rx8		CL22	Call
TCN-JM3200HLE-32GK	32GB KIT JM DDR4 3200Mhz U-DIMM 1Rx8 2Gx8 CL22 1.2V	3200	CL22	Call
U-DIMM Dual Channel Kit (For PC)				
TCN-JM2666HLG-16GK	16GB KIT JM DDR4 2666Mhz U-DIMM 1Rx16	2666	CL19	Call
TCN-JM3200HLG-8G	8GB JM DDR4 3200Mhz U-DIMM 1Rx16 1Gx16 CL22 1.2V	3200	CL22	Call
TCN-JM3200HLE-32G	32GB JM DDR4 3200Mhz U-DIMM 2Rx8 2Gx8 CL22 1.2V	3200	CL22	Call
TS-2666 (TS Series) : Branded chips test 100% (ไม่ระบุ chips) เหมาะกับลูกค้าที่เน้นคุณภาพ / ราคาสูงกว่า JM RAM				
	SO-DIMM (For Notebook)		U-DIMM (For PC)	
SO-DIMM (For Notebook)				
TCN-TS2666HSH-4G	4GB DDR4 2666Mhz SO-DIMM 1Rx8 512Mx8 CL19	2666	CL19	Call
TCN-TS2666HSB-8G	8GB DDR4 2666Mhz SO-DIMM 1Rx8 1Gx8 CL19			Call
TCN-TS2666HSB-16G	16GB DDR4 2666Mhz SO-DIMM 2Rx8 1Gx8 CL19			Call
TCN-TS2666HSE-16G	16GB DDR4 2666Mhz SO-DIMM 1Rx8 2Gx8 CL19	2666	CL19	Call
TCN-TS2666HSE-32G	32GB DDR4 2666Mhz SO-DIMM 2Rx8 2Gx8 CL19			Call
U-DIMM (For PC)				
TCN-TS2666HLH-4G	4GB DDR4 2666Mhz U-DIMM 1Rx8 512Mx8 CL19	2666	CL19	Call
TCN-TS2666HLB-8G	8GB DDR4 2666Mhz U-DIMM 1Rx8 1Gx8 CL19			Call
TCN-TS2666HLB-16G	16GB DDR4 2666Mhz U-DIMM 2Rx8 1Gx8 CL19			Call
TCN-TS2666HSE-16G	16GB DDR4 2666Mhz SO-DIMM 1Rx8 2Gx8 CL19	2666	CL19	Call
TCN-TS2666HLE-32G	32GB DDR4 2666Mhz U-DIMM 2Rx8 2Gx8 CL19			Call
TS Ram (TS Series) : Branded chips test 100% (ระบุ chips) เหมาะกับลูกค้า SI หรืองาน Project / ราคาสูงที่สุด				
	SO-DIMM (For Notebook)		U-DIMM (For PC)	
SO-DIMM (For Notebook)				
TCN-TS512MSH64V4H	4GB DDR4 2400Mhz SO-DIMM 1Rx8 512Mx8 CL17	2400	CL17	Call
TCN-TS1GSH64V4B	8GB DDR4 2400Mhz SO-DIMM 1Rx8 1Gx8 CL17			Call
TCN-TS512MSH64V6H	4GB DDR4 2666Mhz SO-DIMM 1Rx8 512Mx8 CL19	2666	CL19	Call
TCN-TS1GSH64V6B	8GB DDR4 2666Mhz SO-DIMM 1Rx8 1Gx8 CL19			Call
TCN-TS2GSH64V6B	16GB DDR4 2666Mhz SO-DIMM 2Rx8 1Gx8 CL19			Call
TCN-TS4GSH64V6E	32GB DDR4 2666Mhz SO-DIMM 2Rx8 2Gx8 CL19			Call
TCN-TS4GSH72V6E	32GB DDR4 2666Mhz ECC-SO-DIMM 2Rx8 2Gx8 CL19			Call
TCN-TS1GSH64V2B3	8GB DDR4 3200Mhz SO-DIMM 1Rx8 1Gx8 CL22	3200	CL22	Call
U-DIMM (For PC)				
TCN-TS512MLH64V4H	4GB DDR4 2400Mhz U-DIMM 1Rx8 512Mx8 CL17	2400	CL17	Call
TCN-TS1GLH64V4B	8GB DDR4 2400Mhz U-DIMM 1Rx8 1Gx8 CL17			Call
TCN-TS2GLH64V4B	16GB DDR4 2400Mhz U-DIMM 2Rx8 1Gx8 CL17			Call
TCN-TS1GLH64V6B	8GB DDR4 2666Mhz U-DIMM 1Rx8 1Gx8 CL19			Call
TCN-TS2GLH64V6B	16GB DDR4 2666Mhz U-DIMM 2Rx8 1Gx8 CL19			Call
TCN-TS4GLH64V6E	32GB DDR4 2666Mhz U-DIMM 2Rx8 2Gx8 CL19			Call
TCN-TS4GLH72V6E	32GB DDR4 2666Mhz ECC-DIMM 2Rx8 2Gx8 CL19			Call
TCN-TS4GHR72V6C	32GB DDR4 2666Mhz REG-DIMM 2Rx4 2Gx4 CL19			Call
TCN-TS1GLH64V2B3	8GB DDR4 3200Mhz U-DIMM 1Rx8 1Gx8 CL22	3200	CL22	Call
TCN-TS2GLH64V2B3	16GB DDR4 3200Mhz U-DIMM 2Rx8 1Gx8 CL22			Call

LEXAR : DRAM		Lexar™	
Article	Description	SRP Inc VAT	
DRAM			
	LXR-4AS004G-R2666	4GB, DDR4 2666 SO-DIMM, CL19	Call
	LXR-4AS004G-B2666	4GB, DDR4 2666 SO-DIMM, CL19 - Box	Call
	LXR-4AS008G-R2666	8GB, DDR4 2666 SO-DIMM, CL19	Call
	LXR-4AS008G-B2666	8GB, DDR4 2666 SO-DIMM, CL19 - Box	Call
	LXR-4AS016G-R2666	16GB, DDR4 2666 SO-DIMM, CL19	Call
	LXR-4AS008G-B3200	8GB, DDR4 3200 SO-DIMM, CL22	Call
	LXR-4AS016G-R3200	16GB, DDR4 3200 SO-DIMM, CL22	Call
	LXR-4AS032G-B3200	32GB, DDR4 3200 SO-DIMM, CL22 - Box	Call
	LXR-4AU004G-B2666	4GB, DDR4 2666 U-DIMM, CL19 - Box	Call
	LXR-4AU008G-R2666	8GB, DDR4 2666 U-DIMM, CL19	Call
	LXR-4AU008G-B2666	8GB, DDR4 2666 U-DIMM, CL19 - Box	Call
	LXR-4AU016G-R2666	16GB, DDR4 2666 U-DIMM, CL19	Call
	LXR-4AU008G-R3200	8GB, DDR4 3200 U-DIMM, CL22	Call
	LXR-4AU016G-R3200	16GB, DDR4 3200 U-DIMM, CL22	Call
	LXR-4AU032G-R3200	32GB, DDR4 3200 U-DIMM, CL22	Call
	LXR-4BU008GR3600DL	16GBKIT Hades RGB DDR4 3600 UDIMM 8GBx2	Call
	LXR-4BU016GR3600GS	16GB Hades RGB DDR4 3600 UDIMM, 16GBx1	Call
	LXR-4BU016GR3600GD	32GBKIT Hades RGB DDR4 3600 UDIMM 16GBx2	Call
	LXR-4BU008GR3600D0	16GBKIT Hades DDR4 3600 UDIMM, 8GBx2	Call
	LXR-4BU016GR3600GS	16GB Hades DDR4 3600 UDIMM, 16GBx1	Call
	LXR-4BU016GR3600GD	32GBKIT Hades DDR4 3600 UDIMM, 16GBx2	Call
	LXR-5DU016GR4800GS	16GB ARES DDR5 4800 UDIMM Gray 	Call

Crucial : DRAM		New Arrival		crucial™ by Micron	
Article	Description/Spec.	SRP (Inc.VAT)	Warranty		
					
DRAM For PC UDIMM					
CCL-CT4G4DFS8266	Crucial 4GB DDR4 2666 UDIMM CL19	720.00	Limited Lifetime		
CCL-CT8G4DFRA266	Crucial 8GB DDR4-2666 UDIMM CL19	1,090.00	Limited Lifetime		
CCL-CT8G4DFRA32A	Crucial 8GB DDR4-3200 UDIMM CL22	1,090.00	Limited Lifetime		
CCL-CT16G4DFRA266	Crucial 16GB DDR4-2666 UDIMM CL19	1,990.00	Limited Lifetime		
CCL-CT16G4DFRA32A	Crucial 16GB DDR4-3200 UDIMM CL22	1,990.00	Limited Lifetime		
CCL-CT32G4DFD8266	Crucial 32GB DDR4-2666 UDIMM CL19	3,790.00	Limited Lifetime		
					
DRAM For Notebook SODIMM					
CCL-CT4G4SFS8266	Crucial 4GB DDR4 2666 SODIMM CL19	720.00	Limited Lifetime		
CCL-CT8G4SFRA266	Crucial 8GB DDR4-2666 SODIMM CL19	1,090.00	Limited Lifetime		
CCL-CT8G4SFRA32A	Crucial 8GB DDR4-3200 SODIMM CL22	1,090.00	Limited Lifetime		
CCL-CT16G4SFRA266	Crucial 16GB DDR4-2666 SODIMM CL19	1,990.00	Limited Lifetime		
CCL-CT16G4SFRA32A	Crucial 16GB DDR4-3200 SODIMM CL22	1,990.00	Limited Lifetime		
CCL-CT32G4SFD8266	Crucial 32GB DDR4-2666 SODIMM CL19	3,790.00	Limited Lifetime		

All In One Liquid Cooler

ECCOOLER®



Warranty : 3 Years	PCC-GI-CX360-WH	PCC-GI-CX360-BK	PCC-GI-CX240-WH	PCC-GI-CX240-BK
CPU Compatibility	Intel : LGA2066/2011/1150/1151/1155/1156/775/1366 AMD : TR4/AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2			
TDP	350W		250W	
Radiator Dimension	394×120×27mm		274×120×27mm	
Radiator Material	Aluminum		Aluminum	
Water block Dimension	70x80×54.3mm		70x80×54.3mm	
Cold Plate Material	oxygen-free Copper		oxygen-free Copper	
Pump Speed	2600±10%RPM		2600±10%RPM	
RGB Version	AURA 5V 3Pin addressable		AURA 5V 3Pin addressable	
Fan Dimension	120×120×25mm		120×120×25mm	
Included Fans	3pcs		2pcs	
Fan Speed	1000~2000±10%RPM		1000~2000±10%RPM	
Max. Air Flow	72CFM		72CFM	
Max. Static Pressure	2.36mmH2O		2.36mmH2O	
Noise	8~29.1dB(A)		8~29.1dB(A)	
	• Addressable 120mm PWM VortexPro Fan blades Halo • Universal metal EasySET Pro bracket • Crescent addressable RGB LED on liquid cooling block • 8Pcs De-vibration Rubber on Fans • Ultra silent 12-coil 10-Pole three-phase pump motor • Include RGB controller/CPU Block can Rotataion • 149Pcs skiving 0.12mm micro liquid fin channel		• Addressable 120mm PWM VortexPro Fan blades Halo • Universal metal EasySET Pro bracket • Crescent addressable RGB LED on liquid cooling block • 8Pcs De-vibration Rubber on Fans • Ultra silent 12-coil 10-Pole three-phase pump motor • Include RGB controller/CPU Block can Rotataion • 149Pcs skiving 0.12mm micro liquid fin channel	
SRP(inc.VAT)	3,490	3,190	2,690	2,550



Warranty : 3 Years	PCC-GI-CL240VC	PCC-GI-CL120VC
CPU Compatibility	Intel : LGA2066/2011/1150/1151/1155/1156/775/1366 AMD : TR4/AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2	
TDP	250W	180W
Radiator Dimension	276×120×27mm	153×120×27mm
Radiator Material	Aluminum	Aluminum
Water block Dimension	70x80×54.3mm	75x62×40mm
Cold Plate Material	oxygen-free Copper	oxygen-free Copper
Pump Speed	2600±10%RPM	2600±10%RPM
RGB Version	Static LED Color Fan	Static LED Color Fan
Fan Dimension	120×120×25mm	120×120×25mm
Included Fans	2pcs	1pcs
Fan Speed	800~1600±10%RPM	800~1600±10%RPM
Max. Air Flow	65.4CFM	65.4CFM
Max. Static Pressure	2.36mmH2O	2.36mmH2O
Noise	8~30.8dB(A)	8~30.8dB(A)
	• 149Pcs skiving 0.12mm micro liquid fin channel • Universal metal EasySET Pro bracket • 8Pcs De-vibration Rubber on Fans • Ultra silent 12-coil 10-Pole three-phase pump motor	
SRP(inc.VAT)	2,150	1,390



SIS Distribution (Thailand) Public Company Limited
TEL. 02-020-3000
Email address : sis@sisthai.com

บริษัทฯ ขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว

Air Cooler

ECCOOLER®



Warranty : 1 Years	PCC-GI-D66A-HALO	PCC-GI-D56A-HALO	PCC-GI-H58UB
CPU Compatibility	Intel : LGA2066/2011/1150/1151/1155/1156/775/1366 AMD : TR4/AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2	Intel : LGA2066/2011/1150/1151/1155/1156/775/1366 AMD : AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2	Intel : LGA2066/2011/1150/1151/1155/1156/775/1366 AMD : AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2
TDP	230W	160W	240W
Overall Dimension	135(L)X105(W)X160(H)mm	136(L)X79(W)X151(H)mm	134(L)X100(W)X152(H)mm
Heatsink Material	Aluminum	Aluminum	Aluminum
Heat Base Material	55X35mm Aluminum Base with HDT	45X38mm HDT(Heat pipes Direct Touch)	55X35mm HDT(Heat pipes Direct Touch)
Heat Pipes	6X6mm Copper powder heat pipes U type	5X6mm Copper powder heat pipes	5X8mm Copper powder heat pipes U type
Surface Treatment	Anti-oxidation Protective Layer	3*U type + 2*L type Black Plating Anti-oxidation Protective Layer	Full Black Nickel Plating
RGB Version	AURA 5V 3Pin addressable	AURA 5V 3Pin addressable	N/A
Fan Dimension	120x120x25mm	120x120x25mm	120x120x25mm
Included Fans	2pcs	1pcs	1pcs
Fan Speed	1000~2000±10%RPM	1000~2000±10%RPM	1000~1800±10%RPM
Max. Air Flow	72CFM	72CFM	65CFM
Max. Static Pressure	2.36mmH2O	2.36mmH2O	2.15mmH2O
Noise	8~29.1dB(A)	8~29.1dB(A)	8~26.5dB(A)
	• Universal metal EasySET Pro bracket • Heat pipes Direct Touch • Single tower dual fan setting • SilentPro Blades design with Corona LED Frame • Include RGB controller • Two full function PWM Fan • Close Air channel design	• Universal metal EasySET Pro bracket • Heat pipes Direct Touch • Single tower dual fan setting • SilentPro Blades design with Corona LED Frame • Include RGB controller • Two full function PWM Fan • Close Air channel design	• Universal metal EasySET Pro bracket • Single tower dual fan setting • SilentPro Blades design with Corona LED Frame • Full function PWM Fan • Massive heat exchange fin with black plating surface process
SRP(inc.VAT)	1,950	1,490	1,690



Warranty : 1 Years	PCC-GI-X6B-V2	PCC-GI-X5B-V2	PCC-GI-PALADIN400A
CPU Compatibility	Intel : LGA2066/2011/1150/1151/1155/1156/775/1366 AMD : AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2	Intel : LGA2066/2011/1150/1151/1155/1156/775/1366 AMD : AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2	Intel : LGA1200/1150/1151/1155/1156 AMD : AM4
TDP	160W	160W	200W
Overall Dimension	126(L)X85(W)X148(H)mm	126(L)X85(W)X148(H)mm	130(L) X 76(W) X 157(H)mm
Heatsink Material	Aluminum	Aluminum	Aluminum
Heat Base Material	45X38mm HDT(Heat pipes Direct Touch)	45X38mm HDT(Heat pipes Direct Touch)	39.5 X 35mm HDT
Heat Pipes	5X6mm Copper powder heat pipes 3*U+2*L	5X6mm Copper powder heat pipes 3*U+2*L	4X6mm Copper powder heat pipes
Surface Treatment	Black Plating Anti-oxidation Protective Layer	Anti-oxidation Protective Layer	Anti-oxidation Protective Layer + Heatpipe Nickel Plating
RGB Version	N/A	N/A	AURA 5V 3Pin addressable
Fan Dimension	120x120x25mm	120x120x25mm	130.6x130.6x25mm
Included Fans	1pcs	1pcs	1pc
Fan Speed	1000~1800±10%RPM	1000~1800±10%RPM	800~1600±10%RPM
Max. Air Flow	65CFM	65CFM	81CFM
Max. Static Pressure	2.15mmH2O	2.15mmH2O	2.18mmH2O
Noise	8~26.5dB(A)	8~26.5dB(A)	18~28.6dB(A)
	• Black plating surface process • Single tower& fan setting • Full function PWM Fan • Universal metal EasySET Pro bracket • SilentPro Blades design with Corona LED Frame	• Single tower& fan setting • Full function PWM Fan • SilentPro Blades design with Corona LED Frame • Universal metal EasySET Pro bracket	• Fine-tuned heatpipe specifications build good thermal performance • Upgraded mounting kits, user friendly installation • TIM Thermal Conductivity 12.8W/(m·K)
SRP(inc.VAT)	990	790	870

Air Cooler

ECCOOLER®



Warranty : 1 Years	PCC-GI-X4S	PCC-E126M-PRO
CPU Compatibility	Intel : LGA2066/2011/1150/1151/1155/ 1156/775/1366 AMD : AM4/FM2+/FM2/FM1/AM3+/AM3/ AM2+/AM2"	Intel : LGA/1150/1151/1155/1156/775 AMD : AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2
TDP	145W	92W
Overall Dimension	135(L)X80(W)X150(H)mm	126(L)X126(W)X70(H)mm
Heatsink Material	Aluminum	Aluminum
Heat Base Material	45X38mm HDT(Heat pipes Direct Touch)	37X25mm Aluminum
Heat Pipes	4X6mm Copper powder heat pipes	-
Surface Treatment	Anti-oxidation Protective Layer	Black Plating Anti-oxidation Protective Layer
RGB Version	Static mix-colored LED	Static LED color fan(Can't sync with MB)
Fan Dimension	120×120×25mm	120×120×25mm
Included Fans	1pcs	1pcs
Fan Speed	800~1600±10%RPM	1000~1800±10%RPM
Max. Air Flow	65.4CFM	56CFM
Max. Static Pressure	2.05mmH2O	1.25mmH2O
Noise	18~30.8dB(A)	8~26.5dB(A)
	• Universal metal EasySET Pro bracket • Single tower& fan setting • Full function PWM Fan • High Performance blade design with Color LED Fan	• Full function PWM Fan
SRP(inc.VAT)	670	300

CPU FAN

ECCOOLER®



Warranty : 1 Years	PCC-CORONA-3IN1	PCC-HALO-3in1-KIT	PCC-FX-120-3
RGB SYNC Compatibility	ASUS AURA ARGB GIGABYTE RGB FUSION VDG 3Pin	ASUS AURA ARGB GIGABYTE RGB FUSION VDG 3Pin	-
RGB Chip Type	5V Addressable RGB	5V Addressable RGB	-
Hub RGB Input	N/A	N/A	-
Controller power input	12V IDE	12V IDE	-
Accessories	Controller/1-to-3 ARGB Cable/	Controller/1-to-3 ARGB Cable/	-
Cables	1-to-3 PWM Fan Cable/3Pin VDG Cable	1-to-3 PWM Fan Cable/3Pin VDG Cable	-
Fan RGB connector	3Pin Self-lock 5V VCC/DATA-IN/GND	3Pin Self-lock 5V VCC/DATA-IN/GND	3Pin Static LED Color Fan
RGB Version	AURA 5V 3Pin addressable	AURA 5V 3Pin addressable	-
Fan Dimension	120×120×25mm	120×120×25mm	120×120×25mm
Included Fans	3pcs	3pcs	1pcs
Fan Speed	1000~2000±10%RPM	1000~2000±10%RPM	1200±15% RPM
Max. Air Flow	72CFM	72CFM	31.68CFM
Max. Static Pressure	2.36mmH2O	2.36mmH2O	-
Noise	8~29.1dB(A)	8~29.1dB(A)	18 dB(A)
	• 3Pin SRGB fancontains high-quality LED lamp beads with even and soft halo • Dual power supply options more freedom in installation	• Gen2 ARGB 3Pin • 6LED Addressable dual ring frame • VortexPro Fan Blades	• 3Pin SRGB fancontains high-quality LED lamp beads with even and soft halo • Dual power supply options more freedom in installation
SRP(inc.VAT)	1,390	1,090	130



SIS Distribution (Thailand) Public Company Limited
TEL. 02-020-3000
Email address : sis@sisthai.com

บริษัทฯ ขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว

Power Supply Unit		ECCOOLER®	
  			
	PCC-GI-BR500	PCC-GI-BR600	PCC-GI-BR700
Intel Specification	ATX 12V 2.92 / V2.31	ATX 12V 2.92 / V2.31	ATX 12V 2.92 / V2.31
Dimension	160mm(L)*150mm(W)*85mm(H)	160mm(L)*150mm(W)*85mm(H)	160mm(L)*150mm(W)*85mm(H)
Efficiency	80PLUS Bronze/ERP Lot 6 2013	80PLUS Bronze/ERP Lot 6 2013	80PLUS Bronze/ERP Lot 6 2013
Rated Power	500W	600W	700W
Fan size mm	120mm	120mm	120mm
Input Voltage	100-240VAC	100-240VAC	100-240VAC
Protection Functions	OPP/OVP/UVP/SCP/OTP/SPD	OPP/OVP/UVP/SCP/OTP/SPD	OPP/OVP/UVP/SCP/OTP/SPD
Modular	No	No	No
Cable Type	Normal	Normal	Normal
ATX Connector	1	1	1
CPU Connector	1	1	1
PCIe Connector	2	2	2
Floppy Connector	2	2	2
SATA Connector	6	6	6
MTBF	100,000 Hours	100,000 Hours	100,000 Hours
NET.	1.95KG	2.09KG	2.29KG
Warranty	Three years	Three years	Three years
• Design Scheme : Dual switch forward and Synchronous rectification and Active PFC • All Famous Brand Capacitors Are Used • Intelligent temperature control 12CM fan; Low noise, high efficiency • CB CE EAC CCC safety certification • 7-defense power supply:Insect-proof;Anti-vibration;Corrosion-free • Safe from dust;Flame retardant;Resists humidity;Static prevention			
SRP(inc.VAT)	1,750	1,990	2,250
 New			
	PCC-GI-P850		
Intel Specification	ATX 12V 2.92 / V2.31		
Dimension	160mm(L)*150mm(W)*85mm(H)		
Efficiency	80PLUS GOLD/ERP Lot 6 2013		
Rated Power	850W		
Fan size mm	140mm		
Input Voltage	100-240VAC		
Protection Functions	OPP/OVP/UVP/SCP/OCP/OTP/SPD		
Modular	Fully		
Cable Type	Low-Profile, All Black		
ATX Connector	1		
CPU Connector	2		
PCIe Connector	4		
Floppy Connector	10		
SATA Connector	6		
MTBF	100,000 Hours		
NET.	3.32KG		
Warranty	Three years		
• Design Scheme : Full Bridge Resonant Converter &DC to DC&Active PFC • 14 cm ARGB fan lighting support the syn-chronization with mother board • Intelligent temperature control 12CM fan; Low noise, high efficiency • CB CE EAC CCC safety certification • 7-defense power supply:Insect-proof;Anti-vibration;Corrosion-free • Safe from dust;Flame retardant;Resists humidity;Static prevention			
SRP(inc.VAT)	5,450		



Sis Distribution (Thailand) Public Company Limited

TEL. 02-020-3000

Email address : sis@sisthai.com

บริษัทฯ ขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว

PC CASE

ECCOOLER®

สินค้า PC Case ทุกรุ่น
ไม่มี Power Supply ติดตั้ง



PCC-LE300ARGB-BK

PCC-MM200-BK(Black/ without Fan)
PCC-MM200-WH (White/ without Fan)
PCC-MM200-BK-4F(Black/ with Fan)
PCC-MM200-WH-4F(White/ with Fan)

Model	Master LE300 Mesh ARGB
Product Size	453(L)*210(W)*495(H)mm
Hardware Size	410(L)*210(W)*475(H)mm
Product Material	Hardware 0.6mmSPCC+Panel ABS +Tempered Glass
Motherboard Type	E-ATX/ATX/M-ATX/ITX
I/O Port:	USB3.0*1; USB2.0*2; MIC/Audio*1; Headset*1; Power Button*1; LED Button*1
Drive Bays:	3.5" HDD*2pcs; 2.5" SSD*3pcs
Max.CPU Cooler Height	175mm
Max.GPU Length	390mm
Fan Support:	Front:120/140mm*3; Top:120/140mm*3, Rear:120mm*1; PSU Cover 120mm*1
Liquid Cooling Support:	Front:120mm/240mm/ 360mm; Rear:120mm; Top: 240mm/360mm

Model	Platinum MM200 Mesh
Product Size	375(L)*205(W)*427(H)mm
Hardware Size	340(L)*205(W)*411 (H)mm
Product Material	Hardware 0.6mmSPCC+ Panel ABS+Tempered Glass
Motherboard Type	M-ATX/ITX
I/O Port:	USB3.0*1;USB2.0*2;MIC/Audio*1, Power Button,Reset Button,Led Button
Drive Bays:	3.5 HDD*2pcs; 2.5 SSD*3pcs
Max.CPU Cooler Height	170mm
Max.GPU Length	330mm
Fan Support:	Front:120mm*3/140mm*2;Top:120mm*2; Rear:120mm*1; PSU Cover 120mm*2"
Liquid Cooling Support:	Front:120mm/240mm;Rear:120mm; Top: 120mm/240mm

- RGB Led Strip
- Magnetic dust-proof net on top

- Panel design Full ventilation
- Magnetic dust-proof net on top
- Hidden back wiring design

SRP(inc.VAT)	1,690	990	1,150	1,290	1,350
--------------	-------	-----	-------	-------	-------



PCC-MA200-BK (Black/ without Fan)
PCC-MA200-WH (White/ without Fan)
PCC-MA200-BK-4F (Black/ with Fan)
PCC-MA200-WH-4F (White/ with Fan)

PCC-ME200-BK (Black/ without Fan)
PCC-ME200-WH (White/ without Fan)

Model	Diamond MA200 Mesh
Product Size	400(L)*225(W)*475(H)mm
Hardware Size	360(L)*225(W)*455 (H)mm
Product Material	Hardware 0.6mmSPCC+ Panel ABS+Tempered Glass
Motherboard Type	ATX/ITX/M-ATX
I/O Port:	USB3.0*1;USB1.0*2;MIC/Audio*1, Power Button, Reset Button,Led Button
Drive Bays:	3.5 HDD*2pcs; 2.5 SSD*2pcs
Max.CPU Cooler Height	175mm
Max.GPU Length	350mm
Fan Support:	Front:120/140mm*3;Top:120/140mm*2; Rear:120/140mm*1; PSU Cover 120mm*2
Liquid Cooling Support:	Front:120mm/240mm/360mm; Rear:120mm;Top:360mm

Model	Master ME300 Mesh
Product Size	432(L)*225(W)*495(H)mm
Hardware Size	410(L)*225(W)*480 (H)mm
Product Material	Hardware 0.6mmSPCC+ Panel ABS+Tempered Glass
Motherboard Type	E-ATX/ATX/M-ATX/ITX
I/O Port:	USB3.0*1;USB2.0*2;MIC/Audio*1; Power Button,Reset Button,Led Button
Drive Bays:	3.5 HDD*2pcs;2.5 SSD*4pcs
Max.CPU Cooler Height	180mm
Max.GPU Length	390mm
Fan Support:	Front:120/140mm*3;Top:120/140mm*3; Rear:120/140mm*1;PSU Cover 120mm*2
Liquid Cooling Support:	Front:360mm; Rear:120mm;Top:360mm

- All round Heat Dissipation/Dust-proof
- Support vertical installation of graphics card
- Magnetic dust-proof net on top
- Hidden back wiring design

- Special designed for AIO/AIR Coolers
- Advance I/O port
- Magnetic dust-proof net on top
- Ultimate Cable Management

SRP(inc.VAT)	1,300	1,390	1,590	1,690	2,090	2,190
--------------	-------	-------	-------	-------	-------	-------



SIS Distribution (Thailand) Public Company Limited
TEL. 02-020-3000
Email address : sis@sisthai.com

บริษัทฯ ขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว

PC CASE

PC COOLER

สินค้า PC Case ทุกรุ่น
ไม่มี Power Supply ติดตั้ง

PCC-LM200RGB (Black/ without Fan)
PCC-LM200RGB (White/ without Fan)

Model	PLATINUM LM200 MESH
Product Size	362(L)*200(W)*392(H)mm
Hardware Size	320(L)*200(W)*380(H)mm
Product Material	Hardware 0.5mmSPCC+ Panel ABS+Tempered Glass
Motherboard Type	M-ATX/ITX
I/O Port:	USB3.0*1;USB2.0*2;Mic/Audio*1; RGB Control Button*1
Drive Bays:	3.5 HDD*2PCS; 2.5 SDD*2PCS
Max.CPU Cooler Height	160mm
Max.GPU Length	310mm
Fan Support:	Front:120mm*3/140mm*2; Top: 120mm*2; Rear:120mm*1; PSU Cover 120mm*2
Liquid Cooling Support:	Rear:120mm; Top:240mm
	• Unique design with Led Strip on front panel • Magnetic dust-proof net on top • Compact Design but Big Space
SRP(inc.VAT)	1,030 1,090

New

New

PCC-LM300ARGB-PK

PCC-LA200RGB-BK (Black/without Fan)
PCC-LA200RGB-WH (White/without Fan)
PCC-LA200RGB-BK3F (Black/ with Fan)
PCC-LA200RGB-WH3F (White/ with Fan)

Model	PLATINUM LM300P ARGB	Diamond LA200 RGB
Product Size	375(L)*205(W)*427(H)mm	355(L)*182(W)*423(H)mm
Hardware Size	340(L)*205(W)*411 (H)mm	320(L)*182(W)*410 (H)mm
Product Material	Hardware:0.6mmSPCC+Panel ABS +Tempered Glass	Hardware 0.4mmSPCC+Panel ABS +Acrylic side panel
Motherboard Type	M-ATX/ITX	ATX/M-ATX/ITX
I/O Port:	USB3.0*1;USB2.0*2;MIC/Audio*1; Power Button,Reset Button,Led Button	USB3.0*1;USB2.0*2;MIC/Audio*1; Power Button,Reset Button,Led Button
Drive Bays:	3.5 HDD*2pcs; 2.5 SSD*3pcs	3.5 HDD*2pcs;2.5 SSD*3pcs
Max.CPU Cooler Height	170mm	158mm
Max.GPU Length	330mm	310mm
Fan Support:	Front:120mm*3/140mm*2;Top:120mm*2; Rear:120mm*1; PSU Cover 120mm*2	Front:120mm*2;Rear:120mm*1;
Liquid Cooling Support:	Front:120mm/240mm;Rear: 120mm;Top:120mm/240mm	Rear:120mm
	• Personalized Colorful RGB Led Strip • Magnetic dust-proof screen on top	• All round Heat Dissipation/Dust-proof • Transparent Side with Acrylic material • Magnetic dust-proof net on top • Hidden back wiring design
SRP(inc.VAT)	1,390	930 970 1,170 1,190

Sis

Sis Distribution (Thailand) Public Company Limited
TEL. 02-020-3000
Email address : sis@sis-thai.com

บริษัท สวิสสินทรัพย์ จำกัด

เราจำหน่ายสินค้าคอมพิวเตอร์และอุปกรณ์ไอทีชั้นนำ
พร้อมทั้งบริการหลังการขายและติดตั้งระบบคอมพิวเตอร์

ราคา SRP/End user

เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว

Mainboard



บอร์ดชุดปึกค้อย
Biostar TB360 BTC D+
ใส่ได้ 12 การ์ดจอ



1 YEAR
WARRANTY



3 YEARS
WARRANTY



3 YEARS
WARRANTY

BSR-IB36FAHS

TB360-BTC PRO 2.0,ATX,2xDDR4,1xM2,4xSATA
Supports 9th & 8th Generation Intel Core™
Processor
Intel B360 single chip architecture
Support 2-DIMM DDR4-1866/2133/2400/2666 up
to 32G maximum capacity
Support 12 x PCIe 3.0 slots
Support M.2 (6Gb/s) Connector
Support HDMI Connector

BSR-IH31MMHS

H310MHP 3.0,microATX,2xDDR4,4xSATA
Supports 9th & 8th Generation Intel Core™
Processor
Intel H310 single chip architecture
Supports Dual Channel
DDR4 2666/2400/2133/1866 MHz
up to 32 GB Memory
Supports HDMI 4K resolution
Supports GbE LAN
Supports USB 3.2 Gen1

BSR-IB56CMHS

B560MX/E Pro,microATX,4xDDR4,1xM2,4xSATA
Supports 10th/ 11th Generation Intel Core™
Processor
Intel B560 single chip architecture
Supports 4-DIMM DDR4- 2133/ 2400/ 2666/ 2800/
2933/ 3200/ 3600(OC)/ 3733(OC)/ 3800(OC)/
3866(OC)/ 4000+(OC) up to 128 GB Memory
Supports PCIe 4.0
Supports PCIe M.2 4.0 (64Gb/s)
Supports Intel Optane Technology
Supports USB 3.2 Gen1
Supports WiFi 6 module (No WiFi 6 card included)
Supports HDMI 1.4 4K resolution

SRP(inc.VAT) 6,990.-

1,790.-

3,090.-



3 YEARS
WARRANTY



1 YEAR
WARRANTY



1 YEAR
WARRANTY

BSR-IB36FAHS

A32M2,microATX,2xDDR4,1xM2,4xSATA
Support AMD Ryzen CPU / APU
AMD A320 single chip architecture
Support 2-DIMM DDR4-1866/ 2133/ 2400/
2666/ 2933/ 3200(OC) up to 32G
maximum capacity
Support HDMI
Support USB 3.2 Gen1
Support GbE LAN

BSR-IH31MMHS

Supports 8th and 9th Generation
Intel Core Processor
Intel B360 single chip architecture
Supports SO-DIMM DDR4-2666
up to 16G maximum capacity
Supports 8 x PCIe x16 slots
Supports M.2 (16Gb/s) Connector
Supports HDMI Connector

BSR-IB56CMHS

Supports 9th & 8th Generation
Intel® Core™ Processor
Intel H370 single chip architecture
Support 2-DIMM DDR4-1866/2133/2400/2666
up to 32G maximum capacity
Support 17 x PCI-E 3.0 slots
Support M.2 (6Gb/s) Connector
Support HDMI Connector

SRP(inc.VAT) 1,990.-

8,500.-

8,500.-

Power Supply



5 YEARS
WARRANTY



5 YEARS
WARRANTY



2 YEARS
WARRANTY



HKY-P11-700120000R

WD600K(With US AC Cable)
Rated output : 600W
Temperature controlled fan : 12cm
efficiency : 80plus gold(up to 92%)
12V current : 45A
Voltage range : 90-264VAC
back line : support
Connector : 4+4pin, 2*(6+2)Pin4SATA, 2HDD
Recommend Graphic card :
GTX1080,AMD RX VEGA

HKY-P11-700120000R

WD500K(With US AC Cable)
Rated output : 600W
Temperature controlled fan : 12cm
efficiency : 80plus gold(up to 92%)
12V current : 50A
Voltage range : 90-264VAC
back line : support
Connector : 2*(4+4)pin, 2*(6+2)Pin 4SATA, 2HDD
Recommend Graphic card :
RTX2080,RX5700

HKY-P11-700120000R

GX400X (BU560) PC Case
Material: 0.6mm Black SPCC
Hard Disk Slot : 4
2.5" Hard Disk slot : 1
CD-ROM Slot : 1
Motherboard compatibility ATX
Audio Interface : HD
CHASSIS SPECS. 440*205*435mm
USB USB3.0*2/USB2.0*1/Audit Output
Cooling Fan Slot Front 120mm*3,
Rear:120mm*1,left side 120mm*1

SRP(inc.VAT) 2,090.-

1,890.-

999.-



SIS Distribution (Thailand) Public Company Limited
TEL. 02-020-3000
Email address : sis@sisthai.com

บริษัทฯ ขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว

Mainboard



**3 Years
Warranty**
(DOA 14 3u)



**3 Years
Warranty**
(DOA 14 3u)



**3 Years
Warranty**
(DOA 14 3u)

Basic specifications

Plate type :

Chipset :

CPU support :

Memory support :

Extended support

Disk interface :

Graphics card slot :

Other slots :

I/O interface :

USB interface :

Video interface :

Other slots :

**Mainboard MS-iCraft B560M
MXS-MXN560I02N**

m-ATX
Intel B560 chipset
Intel 10/11 generation Core (LGA1200)
Dual channel DDR4, support 2133/2400/2666/
2800/2933/3000/3200/+ Mhz frequency through
XMP & OC

5 x SATA3.0
1 x PCIe 4.0 M.2 slot (PCI-E 4.0,
only supported when
using Intel 11th i5 and above CPU)
1 x PCIe 3.0 M.2 slot
(support PCI-E 3.0 & SATA mode
2 Slots
1 PCIe 4.0 X16 high-speed graphics card slot
1 PCIe 3.0 X16 graphics card slot
1 x PCIe 3.0 X1 slot

4 x USB3.2 Gen1,
2 x USB2.0
HDMI, DP, VGA
1 PCIe 3.0 X16 graphics card slot
1 x PCIe 3.0 X1 slot

**Mainboard MS-Meterstone B560M
MXS-MXN560M01N**

M-ATX
Intel B560 chipset
Intel 10th&11th generation Core (LGA1200)
Dual channel DDR4, support 2133/2400/2666/
2800/2933/3000/3200/+ Mhz frequency through
XMP & OC

D6 x SATA3.0
1 x PCIe 4.0 X4 direct connection
1 x PCIe 3.0 X4 support NVME/Sata
self-switching (this interface uses Sata mode
to conflict with SataG_2)
1 x PCIe 4.0 X16 high-speed graphics slot
1 x PCIe 3.0 X1 slot
1 x PCIe 3.0 X4 open slot

2 x USB2.0
4 x USB3.2 Gen1
VGA, HDMI, DVI

**Mainboard MS-ChallengerB560M
MXS-MXN560C01N**

M-ATX
Intel B560 chipset
Intel 10th and 11th generation Core (LGA1200)
Dual channel DDR4, support 2133/2400/2666/2
800/2933/3000/3200/+ Mhz frequency through
XMP & OC

5 x SATA3.0
1 x PCIe 4.0 X4 processor directly connected to
M.2 interface (2280)
1 x PCIe 3.0 X4 supports NVME/Sata
self-switching interface (22110)

1 x PCIe 4.0 X16 high-speed graphics slot
1 x PCIe 3.0 X1 slot

2 x USB2.0
4 x USB3.2 Gen1

SRP(inc.VAT)

Call

Call

Call



New

**3 Years
Warranty**
(DOA 14 3u)

Basic specifications

Plate type :

Chipset :

CPU support :

Memory support :

Extended support

Disk interface :

Graphics card slot :

I/O interface :

USB interface :

Video interface :

**Mainboard MS-iCraft Z690 WIFI
MXS-ICRAFT-Z690W**

ATX
Intel Z690 Chipset
Intel 12th Generation Core (LGA1700)
DDR5 four slots, Daisy Chain
enhanced wiring

4 SATA3.0, 4 PCIe 4.0 X4,
1 of which supports
NVME/SATA self-switching
1 PCIe 5.0 X16 full-length slot,
1 PCIe 3.0 X4
full-length slot, 3 PCIe 3.0 X1 slots

6 USB3.2 Gen2 ports
(5 Type-A+1 Type-C), 3 USB3.2 Gen1 ports
HDMI, DP

SRP(inc.VAT)

Call



Basic specifications

Plate type :

Chipset :

CPU support :

Memory support :

Extended support

Disk interface :

Graphics card slot :

Other slots :

I/O interface :

USB interface :

Video interface :

**Mainboard MS-iCraft B550M
MXS-MXA550I02W**

M-ATX
AMD B550 chip
Support AMD AM4 APU and AMD Ryzen 5000
processor (เช่น R5 3400G/R3 3200G)
Support dual-channel DDR4 memory
(overclocking up to 4866MHz)

4 x SATAIII interface
2 x M.2 interface (SATAIII/PCI-E standard)
2 x PCI-E graphics slots
Vertical M.2 E-Key wireless network card slot

3 x USB 3.2 Gen 2 Type-A
2 x USB 3.2 Gen 2 Type-C
1 of which is the front interface
2 x USB2.0 interfaces
HDMI, DP

**Mainboard MS-Terminator B550M
MXS-MXA550T01N**

M-ATX
AMD B550 chip
Support AMD AM4 APU and AMD Ryzen
processor (เช่น R5 3400G/R3 3200G)
Support dual-channel DDR4 memory
(XMP 3800MHz)

4 x SATAIII interface
1 x M.2 interface (SATAIII/PCI-E standard)
2 PCI-E graphics slots
1 PCI-E X1 slot

2 x USB3.1 interface
4 x USB2.0 interface

VGA, HDMI

**MS-Challenger A520M
MXS-MXA520C01N**

M-ATX
AMD A520 chip
Support AMD AM4 socket APU and AMD Ryzen
processor
Support dual channel DDR4 memory

4 x SATAIII interface
1x M.2 interface (SATAIII/PCI-E standard)
1 PCI-E graphics card slot x16
1 x PCI-E X1 slot
1 x M.2 slot
2 x USB3.2 Gen1 interface
4 x USB2.0 interface

SRP(inc.VAT)

Call

Call

Call



SIS Distribution (Thailand) Public Company Limited

TEL. 02-020-3000

Email address : sis@sis-thai.com

บริษัท สิส ดิสทริบิวชัน (ประเทศไทย) จำกัด ขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว

VGA CARD



MXS-SN3060OMN12000
MS-GeForce RTX3060 OTES 12G

3 Years Warranty
(DOA 14 3u)

Basic parameters

Chips : GeForce RTX3060
Memory : 12GB GDDR6
Core frequency : 1320 - 1777
Shader(CUDA) : 3584
Video memory frequency : 15GHz
Bus Width : 192bit
Bus Interface : PCIe 4.0 x16
Support : OpenGL 4.6/DirectX 12.2
I/O : 3 x Display port + HDMI
External power supply : 8 pinsx1
Power consumption 170W/550W

3 Years Warranty
(DOA 14 3u)

Basic parameters

Display core :
Stream processor :
Core frequency :
Video memory frequency :
Memory capacity :
Video memory type :
Video memory bit width :
Bus interface type :
I/O :
3D API :



MXS-SN0730TFN02V00
MS-GT730 Transformer2G V0

NVIDIA GeForce GT730
384 pcs
902MHz
5012MHz
2GB
GDDR5
64bit
PCI Express X8 2.0
HDMI+VGA+DVI
DirectX 11
Shader Model 5.0
OpenGL 4.5



MXS-SN0730PHN02V10
MS-GT730 Powerhammer2G V1

NVIDIA GeForce GT730
96 pcs
700MHz
1333MHz
2GB
DDR3
64bit
PCI Express X8 2.0
HDMI+VGA+DVI
DirectX 11
Shader Model 5.0
OpenGL 4.5

SRP(inc.VAT) Call

Call

Call



MXS-RTX3070-TURBO
GeForce RTX3070 turbo 8G W1

Show core : NVIDIA GeForce RTX 3070
Architecture model : Ampere
Core code : GA104
Core technology : 8nm
Stream processor : 5888
Core frequency : 1500MHz
Core dynamic acceleration frequency : 1725MHz
Memory frequency : 14000MHz
Memory capacity : 8GB
Memory type : GDDR6
Memory bit width : 256bit
Memory bit width : PCI Express X16 4.0
Bus interface type : Turbo dual-fan cooling system
Cooling method : DP*3/HDMI
Display interface : 7680x4320 Pixel DisplayPort resolution
Maximum resolution : 2*8Pin power supply
External power supply : Above 220W
TDP : Above 650W
Recommended power supply : DirectX 12, Shader Model 5.0, OpenGL 4.5
System Requirements : Windows 10



MXS-RTX3060-ICRAFT
GeForce RTX3060 iCraft OC 12G S1

NVIDIA GeForce RTX 3060
Ampere
GA104/GA106
8nm
3584
1320MHz
1822MHz
15000MHz
12GB
GDDR6
192bit
PCI Express X16 4.0
New generation iCraft cooling system
DP*3/HDMI
7680x4320 Pixel DisplayPort resolution
8Pin power supply
Above 170W
Above 550W
DirectX 12, Shader Model 5.0, OpenGL 4.5
Windows 10



MXS-GT1030TF2G
VGA GT1030 Transformer 2G

NVIDIA GeForce GT1030
Pascal
GP108
14nm
384
1227MHz
1468MHz
6000MHz
2GB
GDDR5
64bit
48GB/s
PCI Express X4
PWM intelligent temperature control
HDMI+DVI
3840 x 2160 Pixel DisplayPort resolution
30W
200W
DirectX 12, Shader Model 5.0, OpenGL 4.5
Windows 10; Windows 8 & 8.1, Windows 7, Windows Vista, Linux, FreeBSD x86

SRP(inc.VAT) Call

Call

Call

VGA CARD



3 Years Warranty
(DOA 14 3u)

MXS-SA0550TFN04H00
MS-RX550 Transformer 4GH0

Basic parameters

Display core :
Stream processor :
Core frequency :
Video memory frequency :
Memory capacity :
Video memory type :
Video memory bit width :
Video memory bandwidth :
Bus interface type :
Cooling method :
I/O :
3D API :

AMD Redon RX 550
512
1100 ~ 1183MHz
6000MHz
4GB
GDDR5
128bit
112GB/s
PCI Express X8 3.0
PWM intelligent temperature control
HDMI+DP+DVI
DirectX 12
Shader Model 5.0
OpenGL 4.5

SRP(inc.VAT) Call



SIS Distribution (Thailand) Public Company Limited
TEL. 02-020-3000
Email address : sis@sissthai.com

บริษัทขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดของรายละเอียดต่างๆ อันเนื่องมาจากการพิมพ์

ราคา SRP/End user เป็นราคารวมภาษีมูลค่าเพิ่ม 7 % แล้ว

Power Supply

RAIDMAX

500W, 12V Single Rail, Fan Size 12cm
RMX-RX-500AF-VR

3 YRS
WARRANTY



700W, 12V Single Rail, Fan Size 12cm
RMX-RX-700AC-VR

3 YRS
WARRANTY

**Specification :**

ได้มาตรฐาน 80+ Bronze ประสิทธิภาพสูง
Multi-GPU Technology - มาพร้อม connector 6-pin & 8-pin PCIe รองรับ GPU ทุกแพลตฟอร์ม
รองรับการทำงานร่วมกับ CPU แบบ Dual Core, Quad Core and Multi Core CPUs.
มาพร้อมกับพัดลม ARGB ขนาด 120mm ระบายความร้อนอัตโนมัติเพื่อการระบายความร้อนที่เหนือกว่า
ระบบป้องกัน : ป้องกันแรงดันไฟเกิน, ป้องกันจ่ายไฟเกิน, ป้องกันไฟฟ้าลัดวงจร
Dimension : (L)150 x (W)140 x (H)86 mm.

SRP(inc.VAT)

1,790.-

2,190.-

600W, 12V Single Rail, Fan Size 13.5cm
RMX-RX-600AE-M

5 YRS
WARRANTY



800W, 12V Single Rail, Fan Size 13.5cm
RMX-RX-800AE-M

5 YRS
WARRANTY

**Specification :**

80 PLUS® Gold ให้ประสิทธิภาพพลังงาน 90% ที่ภาระโหลดจริง
คาปาซิเตอร์ญี่ปุ่นคุณภาพสูง รับประกันการทำงานพลังงานที่เสถียรและยาวนาน
พัดลมควบคุมความเร็วรอบขนาด 13.5 ซม. เสียงเบาไม่รบกวนการทำงาน
Single +12V rail รองรับการทำงานระดับไฮเอนด์ ให้ความเสถียรสูง ทำงานได้อย่างราบรื่น
OVP, UVP, SCP และ OPP ให้ความปลอดภัยสูงสุดแก่ส่วนประกอบระบบที่สำคัญของคุณ
ตรงตามข้อกำหนด EU ErP ล่าสุด
รองรับมาตรฐาน CE, FCC, TUV, and cTUVus Haswell Ready.

SRP(inc.VAT)

2,750.-

3,190.-